



Actual

Catalog Number: EXSHC0820
Product ID: 7TCA297120R0287
EAN Number: 05011949022706
Status: Active

Liquid Tight Metallic Conduit, Highly Flexible, High Temperature Applications, Conduit Size 50mm, Minimum Bore 40.4mm, Reel Length 20 Meters, Stainless Steel Core with Thermoplastic Rubber Coating, Black

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5543 Liquid Tight Conduit
Brand Name	Kopex
Type	Liquid Tight Metallic Conduit
Application	Connection for Conduit Systems with High Temperature Applications
Standard	IEC61386
Trade Size	50mm
Inside Diameter	40.4mm
Length	20 Meters
Material	Stainless Steel Core and Thermoplastic Rubber Coating
Color	Black

European Specifications (ETIM)

ETIM	EC001179 Protective metallic hose
Nominal diameter	50mm
Nominal size in inch	1 1/2 inch
Inner diameter	40.4mm
Material	Stainless steel
Surface protection	Untreated
Sheathing material 1st coating	Other
Operating temperature	-35-+105°C
Colour	Black
Bending strength	Flexible
Approved according to DIN EN 61386-23 Y	

Packaging

Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	53.44 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com