

**Catalog Number:** FLB0710  
**Product ID:** 7TCA297020R0110  
**EAN Number:** 05011949202689  
**Status:** Active



Actual

Liquid Tight, Medium Flexibility Conduit, Nominal Conduit Size 40mm, 1-1/4 Inch US Trade Size, Outside Diameter 41.8mm, Inside Diameter 35.4mm, Static Bend Radius 180mm, Reel Length 10 Meters, Galvanised Steel Core, String Packing, PVC Covering, Black

## North American Specifications (UNSPSC)

|                  |                                                            |
|------------------|------------------------------------------------------------|
| UNSPSC           | 39131706 Electrical conduit                                |
| IGCC             | 5543 Liquid Tight Conduit                                  |
| Brand Name       | Kopex                                                      |
| Type             | Liquid Tight Metallic Conduit                              |
| Application      | Indoors/Outdoors, Marine, Buildings, Infrastructure        |
| Standard         | BSI Kitemark KM-90009, Low Voltage Directive               |
| Trade Size       | NC 40mm/1-1/4 Inch                                         |
| Outside Diameter | 41.8mm                                                     |
| Inside Diameter  | 35.4mm                                                     |
| Length           | 10 Meters                                                  |
| Radius           | 180mm                                                      |
| Flexibility      | Medium                                                     |
| Material         | Galvanized Steel Core with String Packing and PVC Covering |
| Color            | Black                                                      |

## European Specifications (ETIM)

|                                         |                                   |
|-----------------------------------------|-----------------------------------|
| ETIM                                    | EC001179 Protective metallic hose |
| Nominal diameter                        | 40mm                              |
| Nominal size in inch                    | 1 1/4 inch                        |
| Outer diameter                          | 41.8mm                            |
| Inner diameter                          | 35.4mm                            |
| Material                                | Steel                             |
| Surface protection                      | Untreated                         |
| Sheathing material 1st coating          | PVC                               |
| Operating temperature                   | -20-+105°C                        |
| Degree of protection (IP)               | IP67                              |
| Weight                                  | 0.946kg/m                         |
| Colour                                  | Black                             |
| Bending strength                        | Flexible                          |
| Approved according to DIN EN 61386-23 Y |                                   |

## Packaging

|                           |                 |
|---------------------------|-----------------|
| Outer Quantity            | 1               |
| Outer Dimensions (inches) | 1x1x1           |
| Weight Uom                | 25.38 lbs. Each |

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 8155 T&B Blvd.  
 Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
 MS 3B-50  
 8155 T&B Blvd.  
 Memphis, TN 38125

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)