

Catalog Number: FLH0710
Product ID: 7TCA297020R0150
EAN Number: 05011949203006
Status: Active



Actual

Liquid Tight, High Temperature Conduit, Nominal Conduit Size 40mm, 1-1/4 Inch US Trade Size, Outside Diameter 41.8mm, Inside Diameter 35.4mm, Static Bend Radius 180mm, Reel Length 10 Meters, Galvanised Steel Core, String Packing with Thermoplastic Rubber Covering, Black

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5543 Liquid Tight Conduit
Brand Name	Kopex
Type	Liquid Tight High Temperature Conduit
Application	Extreme Temperature Environments
Standard	BSI Kitemark KM-90009, Low Voltage Directive
Trade Size	NC 40mm/1-1/4 Inch
Outside Diameter	41.8mm
Inside Diameter	35.4mm
Length	10 Meters
Radius	180mm
Flexibility	High
Material	Galvanized Steel Core with String Packing and Thermoplastic Rubber Coating
Color	Black

European Specifications (ETIM)

ETIM	EC001179 Protective metallic hose
Nominal diameter	40mm
Nominal size in inch	1 1/4 inch
Outer diameter	41.8mm
Inner diameter	35.4mm
Material	Steel
Surface protection	Untreated
Sheathing material 1st coating	Megolon, flame retardant
Operating temperature	-50-+130°C
Degree of protection (IP)	IP67
Colour	Black
Bending strength	Flexible
Approved according to DIN EN 61386-23 Y	

Packaging

Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	29.43 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com