

Catalog Number: FLLH0410
Product ID: 7TCA297020R0160
EAN Number: 05011949203082
Status: Active



Actual

Liquid Tight, High Temperature Conduit, Nominal Conduit Size 20mm, 1/2 Inch US Trade Size, Outside Diameter 21.1mm, Inside Diameter 15.9mm, Static Bend Radius 80mm, Reel Length 10 Meters, Galvanised Steel Core, String Packing with Thermoplastic Rubber Covering, Blue

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5543 Liquid Tight Conduit
Brand Name	Kopex
Type	Liquid Tight High Temperature Conduit
Application	Extreme Temperature Environments
Standard	BSI Kitemark KM-90009, Low Voltage Directive
Trade Size	NC 20mm/1/2 Inch
Outside Diameter	21.1mm
Inside Diameter	15.9mm
Length	10 Meters
Radius	80mm
Flexibility	High
Material	Galvanized Steel Core with String Packing and Thermoplastic Rubber Coating
Color	Blue

European Specifications (ETIM)

ETIM	EC001179 Protective metallic hose
Nominal diameter	20mm
Nominal size in inch	1/2 inch
Outer diameter	21.1mm
Inner diameter	15.9mm
Material	Steel
Surface protection	Untreated
Sheathing material 1st coating	Megolon, flame retardant
Operating temperature	-50-+130°C
Degree of protection (IP)	IP67
Weight	0.385kg/m
Colour	Blue
Bending strength	Flexible
Approved according to DIN EN 61386-23 Y	

Packaging

Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	8.25 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com