

Catalog Number: FLT0610
Product ID: 7TCA297020R0185
EAN Number: 05011949214880
Status: Active



Actual

Liquid Tight, Low Fire Hazard Conduit, Nominal Conduit Size 32mm, 1 Inch US Trade Size, Outside Diameter 33.1mm, Inside Diameter 26.7mm, Static Bend Radius 145mm, Reel Length 10 Meters, Galvanised Steel Core, String Packing with LFH Covering, Black

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5543 Liquid Tight Conduit
Brand Name	Kopex
Type	Liquid Tight Low Fire Hazard Conduit
Application	Indoors / Outdoors, Marine, Buildings, & Rail Infrastructure Where Low Smoke and Toxicity are of Concern
Standard	BSI Kitemark KM-90009, Low Voltage Directive, London Underground I-085, NFF16-101 (I1 F1)
Trade Size	NC 32mm/1 Inch
Outside Diameter	33.1mm
Inside Diameter	26.7mm
Length	10 Meters
Radius	145mm
Flexibility	Medium
Material	Galvanized Steel Core with String Packing and Low Fire Hazard Coating
Color	Black

European Specifications (ETIM)

ETIM	EC001179 Protective metallic hose
Nominal diameter	32mm
Nominal size in inch	1 inch
Outer diameter	33.1mm
Inner diameter	26.7mm
Material	Steel
Surface protection	Untreated
Sheathing material 1st coating	Megolon, flame retardant
Operating temperature	-20-+90°C
Degree of protection (IP)	IP67
Weight	0.603kg/m
Colour	Black
Bending strength	Flexible
Approved according to DIN EN 61386-23 Y	

Packaging

Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	18.41 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com