

Catalog Number: FSH0510
Product ID: 7TCA297070R0015
EAN Number: 05011949218673
Status: Active



Actual

Liquid Tight, High Temperature Conduit, Nominal Conduit Size 25mm, 3/4 Inch US Trade Size, Outside Diameter 26.4mm, Inside Diameter 21.0mm, Static Bend Radius 110mm, Reel Length 10 Meters, IP66, IP67 Ratings, Stainless Steel AISI 316L Core, String Packing with Thermoplastic Rubber Covering, Black

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5543 Liquid Tight Conduit
Brand Name	Kopex
Type	Liquid Tight High Temperature Conduit
Application	Extreme Temperature Environments
Standard	BSI Kitemark KM-90009, Low Voltage Directive
Trade Size	NC 25mm/3/4 Inch
Outside Diameter	26.4mm
Inside Diameter	21.0mm
Length	10 Meters
Radius	110mm
Flexibility	High
Material	316 Stainless Steel Core with String Packing and Thermoplastic Rubber Coating
Color	Black

European Specifications (ETIM)

ETIM	EC001179 Protective metallic hose
Nominal diameter	25mm
Nominal size in inch	3/4 inch
Outer diameter	26.4mm
Inner diameter	21mm
Material	Stainless steel
Surface protection	Untreated
Sheathing material 1st coating	Megolon, flame retardant
Operating temperature	-50-+130°C
Degree of protection (IP)	IP67
Weight	0.487kg/m
Colour	Black
Bending strength	Flexible
Approved according to DIN EN 61386-23 Y	

Packaging

Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	9.13 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com