

Catalog Number: FUB0610
Product ID: 7TCA297020R0210
EAN Number: 05011949203549
Status: Active

Liquid Tight, Medium Flexibility Conduit, Nominal Conduit Size 32mm, 1 Inch US Trade Size, Outside Diameter 33.1mm, Inside Diameter 26.7mm, Static Bend Radius 165mm, Reel Length 10 Meters, UL and CSA Listed, Heavy Galvanised Steel Core, Copper Packing with PVC Covering, Black

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5543 Liquid Tight Conduit
Brand Name	Kopex
Type	Liquid Tight Metallic Conduit
Application	Connection for Conduit Systems
Standard	UL E76358, CSA
Trade Size	NC 32mm/1 Inch
Outside Diameter	33.1mm
Inside Diameter	26.7mm
Length	10 Meters
Radius	165mm
Flexibility	Medium
Material	Galvanized Steel Core with Copper Packing and PVC Covering
Color	Black

European Specifications (ETIM)

ETIM	EC001179 Protective metallic hose
Nominal diameter	32mm
Nominal size in inch	1 inch
Outer diameter	33.1mm
Inner diameter	26.7mm
Material	Steel
Surface protection	Untreated
Sheathing material 1st coating	Copper, tinned
Sheathing material 2nd coating (exterior)	PVC
Operating temperature	-20-+105°C
Degree of protection (IP)	IP67
Colour	Black
Bending strength	Flexible
Approved according to DIN EN 61386-23	Y
With approval according to UL	Y
Approved according to CSA	Y

Packaging

Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	35.01 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com