

Catalog Number: FUB0710
Product ID: 7TCA297020R0212
EAN Number: 05011949203563
Status: Active

Liquid Tight, Medium Flexibility Conduit, Nominal Conduit Size 40mm, 1-1/4 Inch US Trade Size, Outside Diameter 41.8mm, Inside Diameter 35.4mm, Static Bend Radius 200mm, Reel Length 10 Meters, UL and CSA Listed, Heavy Galvanised Steel Core, Copper Packing with PVC Covering, Black

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5543 Liquid Tight Conduit
Brand Name	Kopex
Type	Liquid Tight Metallic Conduit
Application	Connection for Conduit Systems
Standard	UL E76358, CSA
Trade Size	NC 40mm/1-1/4 Inch
Outside Diameter	41.8mm
Inside Diameter	35.4mm
Length	10 Meters
Radius	200mm
Flexibility	Medium
Material	Galvanized Steel Core with Copper Packing and PVC Covering
Color	Black

European Specifications (ETIM)

ETIM	EC001179 Protective metallic hose
Nominal diameter	40mm
Nominal size in inch	1 1/4 inch
Outer diameter	41.8mm
Inner diameter	35.4mm
Material	Steel
Surface protection	Untreated
Sheathing material 1st coating	Copper, tinned
Sheathing material 2nd coating (exterior)	PVC
Operating temperature	-20-+105°C
Degree of protection (IP)	IP67
Colour	Black
Bending strength	Flexible
Approved according to DIN EN 61386-23	Y
With approval according to UL	Y
Approved according to CSA	Y

Packaging

Inner Quantity	1
Inner Dimensions (inches)	48x40x50
Outer Quantity	5
Outer Dimensions (inches)	48x40x50
Weight Uom	37.09 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
 www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321

