

Catalog Number: FUG0410
Product ID: 7TCA297020R0222
EAN Number: 05011949203648
Status: On Hold



Actual

Liquid Tight, Medium Flexibility Conduit, Nominal Conduit Size 20mm, 1/2 Inch US Trade Size, Outside Diameter 21.1mm, Inside Diameter 15.9mm, Static Bend Radius 80mm, Reel Length 10 Meters, UL and CSA Listed, Heavy Galvanised Steel Core, Copper Packing with PVC Covering, Grey

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5543 Liquid Tight Conduit
Brand Name	Kopex
Type	Liquid Tight Metallic Conduit
Application	Connection for Conduit Systems
Standard	UL E76358, CSA
Trade Size	NC 20mm/1/2 Inch
Outside Diameter	21.1mm
Inside Diameter	15.9mm
Length	10 Meters
Radius	80mm
Material	Galvanized Steel Core with Copper Packing and PVC Covering
Color	Gray

European Specifications (ETIM)

ETIM	EC001179 Protective metallic hose
Nominal diameter	20mm
Nominal size in inch	1/2 inch
Outer diameter	21.1mm
Inner diameter	15.9mm
Material	Steel
Surface protection	Untreated
Sheathing material 1st coating	Copper, tinned
Sheathing material 2nd coating (exterior)	PVC
Operating temperature	-20-+105°C
Degree of protection (IP)	IP67
Weight	0.52kg/m
Colour	Grey
Bending strength	Flexible
Approved according to DIN EN 61386-23	Y
With approval according to UL	Y
Approved according to CSA	Y

Packaging

Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	11.27 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com