

Catalog Number: KEBF0410
Product ID: 7TCA297050R0124
EAN Number: 05011949220751
Status: Active



Actual

Liquid Resistant, Highly Flexible Conduit, Nominal Conduit Size 20mm, 1/2 Inch US Trade Size, Outside Diameter 21.2mm, Inside Diameter 17.0mm, Static Bend Radius 40mm, Reel Length 10 Meters, IP54, IP65 Rating, Galvanised Steel Core with PVC Jacket, Black

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5535 Electrical conduit
Brand Name	Kopex
Type	Liquid Resistant Conduit
Application	Indoors / Outdoors - Light Industrial, General Purpose, Buildings
Standard	BSI Kitemark KM-90009, Low Voltage Directive
Trade Size	1/2 Inch
Outside Diameter	21.2mm
Inside Diameter	17.0mm
Length	10 Meters
Radius	Static Bend Radius 40mm
Flexibility	High
Material	Galvanized Steel Core with PVC Jacket
Color	Black

European Specifications (ETIM)

ETIM	EC001179 Protective metallic hose
Nominal diameter	20mm
Nominal size in inch	1/2 inch
Outer diameter	21.2mm
Inner diameter	17mm
Material	Steel
Surface protection	Untreated
Sheathing material 1st coating	PVC
Operating temperature	-25-+70°C
Degree of protection (IP)	IP65
Weight	0.314kg/m
Colour	Black
Bending strength	Flexible
Approved according to DIN EN 61386-23 Y	

Packaging

Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	5.84 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com