

Medium, Mogul and Candelabra Base Incandescent Lampholders

Features and Benefits

- Medium-to-medium extenders available in phenolic and porcelain
- Two-piece surface-type lampholders have concealed wiring terminals with wireways for top and continuous wiring

Socket Extensions — Single Circuit

Medium-Medium

Description	Rating	Cat. No.
2-Piece Porcelain; Mounting Hole 1 $\frac{3}{8}$ " Dia. Extension 1 $\frac{1}{4}$ "**	660W 250V	2004
1-Piece Porcelain; Slotted Mounting Hole 1 $\frac{3}{8}$ " Dia. Extension 1 $\frac{1}{4}$ "**	660W 250V	2005
1-Piece Phenolic. Extension 1 $\frac{3}{16}$ "***	660W 250V	2006

*To be used with porcelain sockets only.

**To be used with phenolic sockets only

Mogul-Mogul

Description	Rating	Cat. No.
1-Piece Porcelain. Extension 2 $\frac{3}{8}$ "*	1500W 600V	8647

NOM Certified except where indicated by *

Socket Adapter

Mogul-To-Porcelain Medium

Description	Rating	Cat. No.
1-piece. Meets Fed. Spec. W-L-142a*	660W 250V	8681
Same as above, except 4 KV Pulse-Rated*	660W 250V	8681-400

NOM Certified except where indicated by *

Flanged Adapter*

Description	Rating	Cat. No.
Porcelain E26 male screwshell with leads	660W 250V	165-00P
Same as 165-00P except Phenolic Body	660W 250V	165-000
Same as 165-000 except with solder terminals, less leads	660W 250V	165-001

*UL Recognized Component, File E13396

Continued on next page



2005



8647



8681



165