

Intended Use

Recessed lensed fixture for grid T-bar ceilings.

Features

- 2'x2' and 2'x4' configurations available
- MVOLT (120-277V) instant start ballast

- Acrylic pattern 12 prismatic lens
- Offered with and without lamps and pre-wire

Listings

UL Listed.

TROFFERS



CONTRACTOR
SELECT


ORDERING INFORMATION

Catalog number	Description	Number of lamps	Lamp type	Number of ballasts	Voltage	Ballast	Pre-wired	Lamp included	Lamp color
GT2 MV	2'x4' recessed troffer	2	32	1	120 - 277	NEMA Premium®, instant start	N	N	-
GT2L MV	2'x4' recessed troffer	2	32	1	120 - 277	NEMA Premium®, instant start	N	Y	700 series, 3500K
GT3 2MV	2'x4' recessed troffer	3	32	2	120 - 277	NEMA Premium®, instant start	N	N	-
GT3 MV	2'x4' recessed troffer	3	32	1	120 - 277	NEMA Premium®, instant start	N	N	-
GT3L MV	2'x4' recessed troffer	3	32	1	120 - 277	NEMA Premium®, instant start	N	Y	700 series, 3500K
GT3L41 MV	2'x4' recessed troffer	3	32	1	120 - 277	NEMA Premium®, instant start	N	Y	700 series, 4100K
GT3LW MV	2'x4' recessed troffer	3	32	1	120 - 277	NEMA Premium®, instant start	Y	Y	700 series, 3500K
GT4 2MV	2'x4' recessed troffer	4	32	2	120 - 277	NEMA Premium®, instant start	N	N	-
GT4 MV	2'x4' recessed troffer	4	32	1	120 - 277	NEMA Premium®, instant start	N	N	-
GT4L MV	2'x4' recessed troffer	4	32	1	120 - 277	NEMA Premium®, instant start	N	Y	700 series, 3500K
GT4L41 MV	2'x4' recessed troffer	4	32	1	120 - 277	NEMA Premium®, instant start	N	Y	700 series, 4100K
GT4L41W MV	2'x4' recessed troffer	4	32	1	120 - 277	NEMA Premium®, instant start	Y	Y	700 series, 4100K
GT4LW MV	2'x4' recessed troffer	4	32	1	120 - 277	NEMA Premium®, instant start	Y	Y	700 series, 3500K
GT2U MV	2'x2' recessed troffer	2	32-U lamp	1	120 - 277	NEMA Premium®, instant start	N	N	-

ADDITIONAL INFORMATION

For additional product information, visit www.lithonia.com.

Drawings are for dimensional detail only and may not represent actual mechanical configuration. Dimensions are shown in inches (centimeters) unless otherwise noted.

*Specifications (2x2)*

Length: 24 (61.0)

Width: 24 (61.0)

Depth: 3-1/8 (7.9)

Specifications (2x4)

Length: 48 (121.9)

Width: 24 (61.0)

Depth: 3-1/8 (7.9)

Certain airborne contaminants can diminish integrity of acrylic and polycarbonate. Refer to the Acrylic & Polycarbonate Environmental Compatibility tables on pages 1116-1117 for suitable uses.