

LED WET LOCATION STRIPLIGHT



- Intended Use**
Ideal for damp/wet locations such as outdoor venues, canopies, and locker rooms.
- Features**
- Light gray, fully gasketed polycarbonate housing with stainless steel captive latches to provide a waterproof seal
 - 3/8" wet location fitting provided on one end
 - UV stabilized, high-impact, clear polycarbonate lens for maximum light output and high impact resistance

- High efficiency LEDs with 80% lumen maintenance at 60,000 hours
 - Mounting hardware for surface mounting to ceiling or wall (horizontally or vertically) included
 - Not designed for continuous row mounting or daisy chaining
- Listings**
UL and cUL Listed to U.S. and Canadian Safety Standards. For use in wet locations under covered ceilings. For use in ambient temperatures from -22°F (-30°C) to 77°F (25°C). IP65 rated.

CONTRACTOR
SELECT

ORDERING INFORMATION		Specifications subject to change.						Example: XWMLLED
Catalog number	UPC	Description	Lumens	Wattage	Color temperature	Pallet quantity	Standard carton quantity	
XWMLLED	753573956365	LED wet location striplight	1800	24	4000K, 88 CRI	18	1	

ADDITIONAL INFORMATION For additional product information, visit www.lithonia.com.

SPECIFICATIONS					
ALL DIMENSIONS ARE SHOWN IN INCHES (CENTIMETERS) UNLESS OTHERWISE NOTED					
LUMENS	LENGTH	WIDTH	DEPTH	WEIGHT	COMPARABLE LIGHT SOURCE
1800	47 - 1/2 (120.7)	2 3/8 (6.0)	3 (7.6)	4.4 lbs (2.0 kg)	1 - 32W T8

Certain airborne contaminants can diminish integrity of acrylic and polycarbonate. Refer to the Acrylic & Polycarbonate Environmental Compatibility tables on pages 1116-1117 for suitable uses.

WET LOCATION INDUSTRIAL



- Intended Use**
Designed for low to medium heights. Ideal for application where dirt, dust, humidity, moisture, and cold temperatures are present.
- Features**
- Rugged light gray polycarbonate housing with continuous poured gasket for an airtight seal, keeping out moisture, dust, and humidity
 - Cold rolled steel enclosed wireway included
 - UV stabilized, impact resistant, polycarbonate lens


- 10 snap fit polycarbonate latches provide a tight seal between diffuser and housing
 - Standard electronic ballast, 120-277V, 60 Hz, ensures no flickering and quiet operation
 - Two stainless steel mounting brackets included, which allow for flush or chain mounting (chain not included)
- Listings**
UL Listed to U.S. and Canadian Safety Standards. UL Listed for 25°C ambient and wet locations. IP65 rated.

CONTRACTOR
SELECT

ORDERING INFORMATION		Specifications subject to change.			Example: XWL232 MV
Catalog number	Number of lamps	Lamp type	Voltage	Ballast	
XWL232 MV	2	32W T8	120 - 277	Electronic instant start	
XWL254 MV	2	54T5HO	120 - 277	Electronic program start	

ADDITIONAL INFORMATION For additional product information, visit www.lithonia.com.

Drawings are for dimensional detail only and may not represent actual mechanical configuration. Dimensions are shown in inches (centimeters) unless otherwise noted.



Certain airborne contaminants can diminish integrity of acrylic and polycarbonate. Refer to the Acrylic & Polycarbonate Environmental Compatibility tables on pages 1116-1117 for suitable uses.