


LUTZE TOP-T Locknuts Plastic

Plastic NPT, PG and Metric



Characteristics

- Hexagonal locknut for secure tightening of plastic cable fittings and accessories
- Easy to install
- Temperature range -20°C - +100°C/
-4°F - +212°F
- Max temporary temperature up to +150°C/+300°F

Specifications

Material Polyamide 6, 30% glass fiber reinforced
Color Black RAL 9005
Gray RAL 7001

Flange is imprinted with locknut size for easy identification.

Part No.	Thread	OD - Ø mm	SW mm	H mm
NPT BLACK				
LPNPT38B	NPT 3/8"	25	22	6
LPNPT12B	NPT 1/2"	30.5	27	6
LPNPT34B	NPT 3/4"	37.5	33	6
LPNPT10B	NPT 1"	46.5	41	7
NPT GRAY				
LPNPT38G	NPT 3/8"	25	22	6
LPNPT12G	NPT 1/2"	30.5	27	6
LPNPT34G	NPT 3/4"	37.5	33	6
LPNPT10G	NPT 1"	46.5	41	7
PG BLACK				
LPPG7B	PG 7	21	19	5
LPPG9B	PG 9	24	22	5
LPPG11B	PG 11	26	24	5
LPPG13B	PG 13.5	29	27	6
LPPG16B	PG 16	33	30	6
LPPG21B	PG 21	39	36	7
LPPG29B	PG 29	50	46	7
LPPG36B	PG 36	66	60	8
LPPG42B	PG 42	73	65	8
LPPG48B	PG 48	78	70	8
PG GRAY				
LPPG7G	PG 7	21	19	5
LPPG9G	PG 9	24	22	5
LPPG11G	PG 11	26	24	5
LPPG13G	PG 13.5	29	27	6
LPPG16G	PG 16	33	30	6
LPPG21G	PG 21	39	36	7
LPPG29G	PG 29	50	46	7
LPPG36G	PG 36	66	60	8
LPPG42G	PG 42	73	65	8
LPPG48G	PG 48	78	70	8
METRIC BLACK				
LPM12B	M12x1.5	19.5	18	5
LPM16B	M16x1.5	24.2	22	5
LPM20B	M20x1.5	28.6	26	6
LPM25B	M25x1.5	35.0	32	6
LPM32B	M32x1.5	46.1	41	7
LPM40B	M40x1.5	55.3	50	7
LPM50B	M50x1.5	66.1	60	8
LPM63B	M63x1.5	82.5	75	8
METRIC GRAY				
LPM12G	M12x1.5	19.5	18	5
LPM16G	M16x1.5	24.2	22	5
LPM20G	M20x1.5	28.6	26	6
LPM25G	M25x1.5	35.0	32	6
LPM32G	M32x1.5	46.1	41	7
LPM40G	M40x1.5	55.3	50	7
LPM50G	M50x1.5	66.1	60	8
LPM63G	M63x1.5	82.5	75	8

Specifications are subject to change without prior notice