



Representative

Catalog Number: 0PG1-M
Product ID: 7TBA133430R0031
UPC Number: 78417002172
Status: A

Battery Unit, Battery Type: lead-calcium, Battery Wattage: 18W, Voltage DC: 6V, 120/277VAC, self-powered, no lamps, Housing Colour: mist-white, Battery Run Time (Minimum): 90 minutes

The PG, P12G Series battery units combine reliability, versatility, performance and cost-efficiency in an aesthetically pleasing design. This series is Ideally suited for a wide range of commercial applications.

- Automatic, temperature compensated, pulse-type charger
- High capacity, automatic, dust-tight instantaneous transfer relay
- Low voltage disconnect prevents over discharge of battery
- Automatic brownout protection is provided
- Battery lock-out prevents battery discharge during installation

North American Specifications (UNSPSC)

UNSPSC	39111709 Emergency light unit
IGCC	3940 Emergency light unit
Type	Battery Unit
Application	Commercial
Standard	UL
Wattage	18 W
Voltage Rating	120/277 VAC ; 6 VDC
Battery	Lead-calcium
Battery Runtime	90 minutes
Lamp Type	No lamps
Size	14-5/8 Inches Height x 12-3/4 Inches Width x 3-1/8 Inches Depth
Material	Housing: Steel
Mounting	Wall
Color	Mist-white

European Specifications (ETIM)

ETIM	EC001957 Emergency luminaire
Material housing	Steel
Colour housing	White
Battery quality	Lead
Voltage type	AC/DC
Nominal voltage	120-277V
Width	323.8mm

Packaging

Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	9 lbs. Each

Documents / Support Tools

Technical Drawing / Data Sheet US	Available on Website
Instruction Sheet	Available on Website

For further technical assistance, please contact us...

860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com