




CONDUIT STRAP • TWO-HOLE METAL

- Two-hole metal straps are designed for use on loads too heavy to be supported by one-hole Jiffy Clips.
- Pre-galvanized steel, except for 280, 290, 292 and 294 which are zinc plated.
- Available in zinc plated steel or made from stainless steel for corrosive environments.
- Also available in brass or hot-dipped galvanized steel. Call customer service for pricing and minimum order quantities.
- For information on Plastic Two-Hole Straps, available in nine sizes, turn to page 210.



Fits EMT	Fits Rigid & IMC	A	B	C	Bolt E	Part #	Std Pkg
Pre-Galvanized							
—	¼	.035	.625	1.765	⅛	225 ★	100
—	⅜	.035	.750	2.515	⅜	228 ★	100
½	—	.035	.750	2.558	⅜	230 ★	100
—	½	.035	.750	2.565	⅜	240 ★	100
¾	—	.035	.750	2.765	⅜	245 ★	100
—	¾	.035	.750	2.795	⅜	250 ★	100
1	—	.035	.750	3.205	⅜	255 ★	100
—	1	.035	.750	3.140	⅜	260 ★	100
1¼	—	.050	.875	3.875	¼	265 ★	100
—	1¼	.050	.875	4.375	¼	270 ★	100
1½	—	.050	1.000	4.300	¼	275 ★	100
—	1½	.060	1.000	4.585	¼	280* ★	100
2	—	.050	1.000	5.000	¼	285 ★	100
—	2	.060	1.250	5.030	⅝	290* ★	50
2½	2½	.060	1.250	6.125	⅝	292* ★	50
3	3	.090	1.250	7.438	⅝	294* ★	25
Stainless Steel (Type 304)							
½	—	.035	.750	2.558	⅜	230SS ★	100
—	½	.035	.750	2.565	⅜	240SS ★	100
¾	—	.035	.750	2.765	⅜	245SS ★	100
—	¾	.035	.750	2.795	⅜	250SS ★	100

*Zinc plated

★ Made in USA

⚡ Harsh Environment Product