




SWITCHES

Rocker Switches





D.P.S.T



D.P.D.T

Terminal Positions

CAT. NO.	CIRCUIT FUNC.	POLES & THROWS	RATINGS			VOLTAGE	LAMP COLOR	ACTR. CONTACT	CONN. TYPE	STD. CTN. QTY.
			AMPS 125VAC	AMPS 250VAC	HP 125-250VAC					
77010RQ	ON-OFF	DPST	20	10	1 1/2 @125,2 @ 250	Non-Lighted	Black	Maintained	0.250 Quikconnect	5
77040RQ	ON-ON	DPDT	20	10	1 1/2 @125,2 @ 250	Non-Lighted	Black	Maintained	0.250 Quikconnect	5
77060RQ	ON-OFF-ON	DPDT	20	10	1 1/2 @125,2 @ 250	Non-Lighted	Black	Maintained	0.250 Quikconnect	5
77130RQ	ON-OFF-ON	DPDT	15	10	3/4	Non-Lighted	Black	Momentary	0.250 Quikconnect	5
Dimensions (IN) A: 1.348 B: 0.750 C: 0.762 D: 0.422										



S.P.S.T

Terminal Positions

CAT. NO.	CIRCUIT FUNC.	POLES & THROWS	RATINGS			VOLTAGE	LAMP COLOR	ACTR. CONTACT	CONN. TYPE	STD. CTN. QTY.
			AMPS 125VAC	AMPS 250VAC	HP 125-250VAC					
77140RQ	ON-OFF	SPST	15	10	—	Non-Lighted	Black	Maintained	0.250 Quikconnect	5
Dimensions (IN) A: 1.250 B: 0.625 C: 0.828 D: 0.406										