

DIGITAL

Auto OFF Countdown Timer

Commercial & Residential In-Wall

SS Series



APPLICATIONS

- Bathroom fans and lights, Indoor/Outdoor lighting.
- Storage areas, hospitality areas.

FEATURES

- **Variable Timing:** Choose from 1 minute to 18 hours.
- **Flash Warning:** "F" suffix models with flicker feature turns load off for 1/2 second, 2 minutes before end of timed cycle and again 1 minute before end of timed cycle.
- **Audible Warning:** "B" suffix model with beep feature will begin a 1/2 second audible warning every 12 seconds during the last 2 minutes of timed cycle.
- **Tamper Resistant:** Time ON interval preset is hidden behind wall plate.
- **Easy Set:** Small screw driver adjustment provides quick set-up of timing.
- **Easy Wiring:** No neutral needed, great for retrofit.

SPECIFICATIONS

- **Timing Accuracy:** $\pm 5\%$ @ 60° to 80°F.
- **Wire Size:** #18AWG
- **Operating Temperature:** 0 °F to +100 °F (-17 °C to +37 °C).
- **Switch Type:**
 - SS13F/SS13B: 3-Way switch with no re-wiring.
 - SS20/SS20F: SPST
- Not compatible with compact fluorescent lamps (CFL) and electronic fluorescent ballasts.

WIRING DIAGRAMS

- See Pages 377-388 For Diagrams.

CAT. NO.	COLOR	CERTIFICATION	UPC CODE	SUPPLY VOLTAGE VAC 50/60Hz	MINIMUM LOAD	WARNING BEFORE TIME OUT	RATINGS			
							RESISTIVE	BALLAST	TUNGSTEN	MOTOR
SS13F	White	cULus	14007	24 120 208	6W @ 24V 30W @ 120V 50W @ 208V	Flicker	.25-4.0A @ 24VAC	.25-4.0A @ 120VAC	.25-4.0A @ 208VAC	1/8 HP @ 120VAC 1/3 HP @ 240VAC
SS13B	White	cULus	14006	240 277	60W @ 240V 70W @ 277V	Beep				
SS20	White	cULus	14005	24 120 208	12W @ 24V 60W @ 120V 105W @ 208V	None	.50-7.25A @ 24VAC	.50-7.25A @ 120VAC	.50-4.0A @ 208VAC	1/6 HP @ 120VAC 1/2 HP @ 240VAC
SS20F	White	cULus	14008	240 277	120W @ 240V 150W @ 277V	Flicker				