



Ocal[®]

Elbows-PVC Coated
T&B Catalog Number:

UPC Number:

Status:

Description:

ELL445-G

70450837075

Active

4 in. x 45 degree Dark Gray 40 mil PVC Coated Hot-Dip Galvanized Rigid Steel Elbow.

Features

	A minimum .040 in. (40 mil) PVC coating on the exterior.
	A nominal .002 in. (2 mil) blue urethane on the interior.
	Ocal-Blue standard radius elbows are factory bent to reduce the time and wasted materials that can result from field bending.
	Color coded thread protectors on each end.

General

Material	Steel
Finish	Hot Dip Galvanized
Color	Dark Gray

Dimension Information

Pipe Size (Metric Size Designator*)	103
Size (inches)	4
Degree of Bend	45

Technical Information

Chemical Resistance Chart	Available on Website
---------------------------	----------------------

Specifications

Ocal Specification Guide-1995 Master Format-PDF	Available on Website
Ocal Specification Guide-1995 Master Format-DOC	Available on Website
Ocal Specification Guide-2004 Master Format-PDF	Available on Website
Ocal Specification Guide-2004 Master Format-DOC	Available on Website

Packaging

Package in Units	1
T&B Sold in UOM	Each
T&B Weight Per UOM	32 lbs. Each

Application Support

Ocal PVC Coated Conduit System	Available on Website
Ocal Specifications	Available on Website
Recommended Installation Procedures	Available on Website
NEMA Standards-RN 1	Available on Website
	Available on Website

NEC 310-16 - Conductors for General
Wiring

NEC Table 8

Available on Website

Notes

Metric size designator (ANSI C80. 1-1994)

Dimensional values are of uncoated elbows.

Certifications

RoHS Compliance

No

Certifications



File Nbr:

E 46453

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com