



Ocal[®]

Conduit Fittings-PVC Coated

T&B Catalog Number:

UPC Number: ST290-G
 Status: 70450840735
 Description: Active

2 in. Dark Gray PVC Coated 90 degree Liquidtight Connector. Fitting material-Steel.

Features

A minimum of .040 in. (40 mil) PVC coating is bonded to the exterior.

Double coated with a nominal .002 in. (2 mil) blue urethane on both the interior and exterior, before PVC coating is applied.

Pressure-sealing sleeves are designed to protect the connection.

PVC coated connectors are available in straight, 45 degree and 90 degree configurations

Ocal uses T&B Industrial Liquidtight fittings to insure quality installations.

Application

To positively bond conduit to box or enclosure

General

Custom_Finish	It_2_90
Trade Size (inches)	2
Material	Steel
Finish	PVC Coated
Color	Dark Gray

Dimension Information

Pipe Size (Metric Size Designator*)	53
Dimension A (inches)	3 1/4
Dimension B (inches)	3 7/16
Dimension C (inches)	7/8

Technical Information

Chemical Resistance Chart	Available on Website
---------------------------	----------------------

Specifications

Ocal Specification Guide-1995 Master Format-PDF	Available on Website
Ocal Specification Guide-1995 Master Format-DOC	Available on Website
Ocal Specification Guide-2004 Master Format-PDF	Available on Website
Ocal Specification Guide-2004 Master Format-DOC	Available on Website

Packaging

Package in Units	6
------------------	---

T&B Sold in UOM	Each
T&B Weight Per UOM	2.85 lbs. Each

Application Support

Ocal PVC Coated Conduit System	Available on Website
Ocal Specifications	Available on Website
Recommended Installation Procedures	Available on Website
NEMA Standards-RN 1	Available on Website
NEC 310-16 - Conductors for General Wiring	Available on Website
NEC Table 8	Available on Website

Notes

Dimensional values are of uncoated liquidtight fittings.

Metric size designator (ANSI C80. 1-1994)

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com