


Conduit Fittings-PVC Coated
T&B Catalog Number:

UPC Number: ST3/4-G
Status: 70450843904
Description: Active

3/4 in. Dark Gray PVC Coated Straight Liquidtight Connector. Fitting material-Steel.

Features

	A minimum of .040 in. (40 mil) PVC coating is bonded to the exterior.
	Double coated with a nominal .002 in. (2 mil) blue urethane on both the interior and exterior, before PVC coating is applied.
	Pressure-sealing sleeves are designed to protect the connection.
	PVC coated connectors are available in straight, 45 degree and 90 degree configurations
	Ocal uses T&B Industrial Liquidtight fittings to insure quality installations.

Application

	To positively bond conduit to box or enclosure
--	--

General

Custom_Finish	lt_34_s
Trade Size (inches)	3/4
Material	Steel
Finish	PVC Coated
Color	Dark Gray

Dimension Information

Pipe Size (Metric Size Designator*)	21
Dimension A (inches)	1 21/32
Dimension B (inches)	1 5/8
Dimension C (inches)	9/16

Technical Information

Chemical Resistance Chart	Available on Website
---------------------------	----------------------

Specifications

Ocal Specification Guide-1995 Master Format-PDF	Available on Website
Ocal Specification Guide-1995 Master Format-DOC	Available on Website
Ocal Specification Guide-2004 Master Format-PDF	Available on Website
Ocal Specification Guide-2004 Master Format-DOC	Available on Website

Packaging

Package in Units	50
------------------	----

T&B Sold in UOM	Each
T&B Weight Per UOM	0.3 lbs. Each

Application Support

Ocal PVC Coated Conduit System	Available on Website
Ocal Specifications	Available on Website
Recommended Installation Procedures	Available on Website
NEMA Standards-RN 1	Available on Website
NEC 310-16 - Conductors for General Wiring	Available on Website
NEC Table 8	Available on Website

Notes

Dimensional values are of uncoated liquidtight fittings.

Metric size designator (ANSI C80. 1-1994)

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com