

TRAY CABLE

PVC Jacket

PVC/Nylon Insulation

90C -600 Volt -UL Type TC-ER*

Method 4 Color code



CONSTRUCTION	
Conductor	- Bare, annealed copper per ASTM B3 - Class B stranding per ASTM B8
Insulation	- Flame-retardant Polyvinyl Chloride (PVC) with clear Polyamide (nylon)
Jacket	- Black, sunlight-resistant, flame-retardant Polyvinyl Chloride (PVC) with ripcord

Applications:

- In free air, raceways, and direct burial
- In wet or dry locations
- Approved for direct burial
- Class 1, Division 2 industrial hazardous locations per NEC
- Permitted for Exposed Run (ER) use in accordance with NEC

Standards:

- UL 83 NEC Type THHN/THWN conductors
- UL 1277 Type TC-ER for 3 conductors or more

Part #	AWG	Conductors	Jacket Thickness	Nom. O.D.	Lbs./M'
A10802	8	2	.060"	.575"	201
A10803	8	3	.060"	.588"	262
A10602	6	2	.060"	.645"	272
A10603	6	3	.060"	.680"	373

*Fittings are available for these products.

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.

*ER Rating only applies to 3 conductors or more.

COLOR CODE CHART

Cond. #	Color
1	Black, printed number
2	Black, printed number
3	Black, printed number