

SPECIFICATION & FEATURES

4" ROUND COVERS FLAT OR DRAWN

DESCRIPTION:

Orbit Industries' Round Covers are used to cover and protect wires in the box. Orbit Industries offers a variety of designs to accommodate many types of electrical devices. Selected models are raised, with open covers and ears.

CERTIFICATION:

UL file E227970, conforms to UL514A. acceptable for use in 2-hour fire rated walls.

FEATURES

K: 1/2" K.O.



MKO: Moon K.O. (1/2" and 3/4" K.O.)

TS: Toggle Switch

DR: Duplex Receptacle


SR: Single Receptacle

PO: Power Outlet



CONFIGURATION DATA

Catalog No.	Description	Cu. In	Std. Pkg.
4RBC	Flat, Blank (Octagonal)	-	50
4RBC-R*	Flat, Blank (Round)	-	50
4RBCK	Flat, 1/2" KO	-	50
4RBC-MKO	Flat, MKO	-	50
4RC-TS	Flat, Toggle Switch	-	50
4RC-DR	Flat, Duplex Receptacle	-	50
4RC-SR	Flat, 1.4" Dia. Single Receptacle	-	50
4RC-PO	Flat, 1.6" Dia. Power Outlet	-	50
4R000X*	Flat, Open, Ears 2-3/4" O.C., Dual Dir.	-	50
4R000S*	Flat, Open, Ears 2-3/4" O.C. Universal Mounting	-	25
4R050X*	Raised 1/2", Open, Ears 2-3/4" O.C., Dual Dir.	3.0	50
4R058X*	Raised 5/8", Open, Ears 2-3/4" O.C., Dual Dir.	4.0	50
4R075X*	Raised 3/4", Open, Ears 2-3/4" O.C., Dual Dir.	5.0	50
4R100X*	Raised 1", Open, Ears 2-3/4" O.C., Dual Dir.	6.8	25
4R125X*	Raised 1-1/4", Open, Ears 2-3/4" O.C., Dual Dir.	8.5	25
4R150X*	Raised 1-1/2", Open, Ears 2-3/4" O.C., Dual Dir.	9.7	25
4R200X*	Raised 2", Open, Ears 2-3/4" O.C., Dual Dir.	12.9	25
4R1000*	Flat, 1-Gang Device Ring	-	50
4R1058*	Raised 5/8", 1-Gang Device Ring	3.5	50



Covers use with 40 boxes (Except 4R000S)

* Also fits 4" Concrete Boxes

