

4-11/16" SQUARE (5S) BOXES

WELDED
2-1/8" DEEP

42.0 Cu. In.

BX/MC CLAMP


- ▶ All MC series boxes are suitable for use with MCAP™-Aluminum
- ▶ MCAP is a trademark of Southwire Company

METAL STUD BRACKET


- ▶ U.S. Patent No.: 8,262,043 Metal Stud (MS) Bracket Engages On Either Side Of A Metal Stud

****Model Revised Feb. 2008**


Cat. No.	Bracket & Setback	Knockouts		Std. Pkg.
		Sides	Bottom	
5SDB-MC	-	6 - MKO, 4 - Loom	3 - 1/2", 2 - 3/4"	24
5SDB-MC-FB	FB, Flush	3 - MKO, 4 - Loom	3 - 1/2", 2 - 3/4"	24
5SDB-MC-MS**	MS, Self-Gripping + Box Support Clip	3 - MKO, 4 - Loom	3 - 1/2", 2 - 3/4"	24
5SDB-MC2-MS**	MS, Self-Gripping + Box Support Clip	1 - MKO, 8 - Loom	1 - MKO	24




5SDB-MC



5SDB-MC-FB



5SDB-MC-MS**



5SDB-MC2-MS**

4-11/16" SQUARE (5S) LARGE CAPACITY BOX

WELDED
2-1/2" DEEP

49.4 Cu. In.


WITH RAISED GROUND EMBOSS & TWO #8-32 x 1/2" MOUNTING SCREWS

PRODUCT FEATURES

- ▶ Suitable for Datacom & Electrical Applications
- ▶ *Durable Blue Powder Coat Finish



Cat. No.	Knockouts		Std. Pkg.
	Sides	Bottom	
5SLB-2MKO	4 - 3/4" & 1" MKO 4 - 1" & 1-1/4" MKO	2 - 1/2", 2 - 3/4"	24
*B-5SLB NEW	4 - 3/4" & 1" MKO 4 - 1" & 1-1/4" MKO	2 - 1/2", 2 - 3/4"	24



5SLB-2MKO

NEW


*B-5SLB


4-11/16" SQUARE (5S) COVERS

FLAT OR DRAWN


NOTE

- ▶ *Available in Durable Red Powder Coat Finish, see page A24


Cat. No.	Description	Cu. Inch	Std. Pkg.
*5BC	Flat, Blank	-	50
5BCK	Flat, 1/2" KO	-	50
5BC-MKO	Flat, MKO	-	50
53000	Flat, Open, Ears 2-3/4" O.C.	-	50
53050	Raised 1/2", Open, Ears 2-3/4" O.C.	3.0	50
53058	Raised 5/8", Open, Ears 2-3/4" O.C.	4.0	50
53075	Raised 3/4", Open, Ears 2-3/4" O.C.	5.0	50
53100	Raised 1", Open, Ears 2-3/4" O.C.	6.8	25
53125	Raised 1-1/4", Open, Ears 2-3/4" O.C.	8.8	25
53150	Raised 1-1/2", Open, Ears 2-3/4" O.C.	9.7	25
53200	Raised 2", Open, Ears 2-3/4" O.C.	12.9	25




*5BC




5BCK



5BC-MKO



53000


 53050
 53058
 53075
 53100
 53125
 53150
 53200

- ▶ **600V** MKO's and CKO's suitable for bonding without any additional bonding means up to 600V
- ▶ Visit www.ul.com or QCIT Guide on page W1 for more information