

# SPECIFICATION & FEATURES

# SIMPLE SUPPORT BRACKET & UNIVERSAL MOUNTING ADAPTER

## DESCRIPTION:

Orbit's latest innovation, the Simple Support Bracket, SSB, works alongside Orbit's Universal Mounting Adapter, UMA, and Stud Mounting Adjustable Ring Series, WBAR1G and 2G to form a versatile Stud Bracket System. This system provides the installer with a solution for mounting boxes and devices between studs.

## CERTIFICATION:

UL file E310661, conforms to UL514A

## FEATURES:

- Telescoping bracket adjusts from 15" to 25"
- SSB assemblies ready to install out of the box with choice of box size and 10" Pigtail, saving time and reducing injuries
- SSB-TBAR includes two riveted clips for T-bar drop ceiling installation. Tek screw provisions on each clip help comply with NEC 314.23 (D) (1)
- T-bar grid clips on SSB-TBAR also include seismic wiring holes to meet earthquake codes
- UMA can either mount-to-stud directly or clip onto bracket
- Rigidity eliminates need for far-side back support
- Markings on Bracket allow for quick and consistent adjustability



SSB-4S-MKO



SSB



UMA



## CONFIGURATION DATA:

| Part No.   | Description                                                                                 | Sides K.O.                | Bottom K.O.               | Std.Pkg. |
|------------|---------------------------------------------------------------------------------------------|---------------------------|---------------------------|----------|
| SSB        | Simple Support Bracket adjusts from 15" to 25" for mounting boxes horizontally between stud | -                         | -                         | 25       |
| SSB-TBAR   | SIMPLE SUPPORT BRACKET WITH T-BAR DROP CEILING MOUNTING CLIPS                               | -                         | -                         | 20       |
| SSB-4S     | Preassembled SSB with UMA and 4" (4S) 2-1/8" Deep Box with 10" Ground Pigtail               | (8) - 1/2",<br>(4) - 3/4" | (2) - 1/2",<br>(2) - 3/4" | 12       |
| SSB-4S-MKO | Preassembled SSB with UMA and 4" (4S) 2-1/8" Deep Box with 10" Ground Pigtail               | (8) - 1/2",<br>(4) - MKO  | (2) - 1/2",<br>(2) - MKO  | 12       |
| SSB-5S-MKO | Preassembled SSB with UMA and 4-11/16" (5S) 2-1/8" Deep Box with MKO and 10" Ground Pigtail | (2) - 1/2",<br>(10) - MKO | (2) - 1/2",<br>(2) - MKO  | 12       |
| UMA        | Universal Mounting Adapter for mounting 4S and 5S boxes to SSB, USB, and directly to stud   | -                         | -                         | 25       |

\*SSB must be accompanied with either UMA, WBAR1G or WBAR2G mounting brackets to attach a steel box



SSB



SSB-TBAR



SSB-4S  
SSB-4S-MKO



SSB-5S-MKO



UMA

