



T8 900 Series Rapid Start

F32T8/TL 950 25PK

Philips leads the industry with the lowest level mercury technology. Reducing the mercury level (source reduction) during the manufacturing phase is essential to creating products that are less harmful to the environment.


Product data

General Information		Color Rendering Index (Nom)		98
Cap-Base	G13 [Medium Bi-Pin Fluorescent]	Operating and Electrical		
Life To 50% Failures (Nom)	15000 h	Power (Rated) (Nom)	31.3 W	
Life To 50% Failures Preheat (Nom)	20000 h	Lamp Current (Nom)	0.265 A	
Life 3-Hr Start [Hrs]	20000 h	Voltage (Nom)	139 V	
Life 12-Hr Start [Hrs]	20000 h	Controls and Dimming		
Light Technical		Dimmable	Yes	
Color Code	TL950 [CCT of 5000K (950)]	Approval and Application		
Luminous Flux (Nom)	2000 lm	Energy Efficiency Label (EEL)	B	
Color Designation	TL950	Mercury (Hg) Content (Nom)	5.0 mg	
Lumen Maintenance 10000 h (Nom)	84 %	Product Data		
Lumen Maintenance 2000 h (Nom)	90 %	Order product name	F32T8/TL950 SLV	
Lumen Maintenance 5000 h (Nom)	89 %	EAN/UPC - Product	046677209056	
Design Mean Lumens	1860 lm	Order code	209056	
Chromaticity Coordinate X (Nom)	342	Numerator - Quantity Per Pack	1	
Chromaticity Coordinate Y (Nom)	352	Numerator - Packs per outer box	25	
Correlated Color Temperature (Nom)	5000 K			
Luminous Efficacy (rated) (Nom)	63.9 lm/W			

T8 900 Series Rapid Start

Material Nr. (12NC)	927942009520
Net Weight (Piece)	137.500 g

Dimensional drawing



Product
F32T8/TL950 SLV

F32T8/TL950

Photometric data

