



T5 Standard

F35T5/841 40PK

Philips T5 Fluorescent Lamps featuring ALTO® Lamp Technology offer increased energy savings and low toxicity in a slim profile.

Product data


General Information		Color Rendering Index (Nom)	
Cap-Base	G5 [G5]	LLMF 2000 h Rated	82
Life To 50% Failures Preheat (Nom)	24000 h	LLMF 4000 h Rated	96 %
Features	HE Alto® [High Efficiency Alto]	LLMF 6000 h Rated	95 %
System Description	High Efficiency	LLMF 8000 h Rated	94 %
LSF Preheat 2000 h Rated	99 %	LLMF 12000 h Rated	93 %
LSF Preheat 4000 h Rated	99 %	LLMF 16000 h Rated	92 %
LSF Preheat 6000 h Rated	99 %	LLMF 20000 h Rated	91 %
LSF Preheat 8000 h Rated	99 %		90 %
LSF Preheat 16000 h Rated	97 %		
LSF Preheat 20000 h Rated	84 %		
Light Technical		Operating and Electrical	
Color Code	841 [CCT of 4100K]	Power (Rated) (Nom)	35.5 W
Initial lumen (Nom)	3650 lm	Lamp Current (Nom)	0.175 A
Luminous Flux (Rated) (Nom)	3325 lm		
Color Designation	Cool White (CW)		
Luminous Efficacy (@ Max Lumen, Rated) (Nom)	105 lm/W		
Chromaticity Coordinate X (Nom)	380		
Chromaticity Coordinate Y (Nom)	380		
Correlated Color Temperature (Nom)	4100 K		
Luminous Efficacy (rated) (Nom)	94 lm/W		
Color Rendering Index (Max)	85		
Color Rendering Index (Min)	80		
		Temperature	
		Design Temperature (Nom)	35 °C
		Controls and Dimming	
		Dimmable	Yes
		Mechanical and Housing	
		Cap-Base Information	Green Plate
		Approval and Application	
		Energy Efficiency Label (EEL)	A

T5 Standard

Mercury (Hg) Content (Nom)	1.4 mg
Product Data	
Order product name	F35T5/841 40PK
EAN/UPC - Product	046677230951
Order code	230953
Numerator - Quantity Per Pack	1

Numerator - Packs per outer box	40
Material Nr. (12NC)	927992784022
Net Weight (Piece)	128.700 g
ILCOS Code	FDH-35/40/1B-L/P-G5-16/1450

Dimensional drawing



Product	D	A	B	B	C
F35T5/841 40PK	17 mm	1449.0 mm	1456.1 mm	1453.7 mm	1463.2 mm

TL5 HE F35T5/841 HE A/to

