



Ceramalux Instant Restrike

C250S50/2 12PK

Dual arc-tube delivers 40,000 hour rated average life as compared to 24,000 hour rated average life for standards HPS lamps. Ideal for industrial applications, warehouses, post top applications and parking lots.

Product data

General Information	
Cap-Base	E39 [Single Contact Mogul Screw]
Operating Position	Universal [Universal]
Main Application	General and Street Lighting
ANSI Code HID	S50
Light Technical	
Luminous Flux (Rated) (Min)	25650 lm
Luminous Flux (Rated) (Nom)	28500 lm
Design Mean Lumens	24750 lm
Chromaticity Coordinate X (Nom)	521
Chromaticity Coordinate Y (Nom)	415
Correlated Color Temperature (Nom)	2100 K
Luminous Efficacy (rated) (Min)	102.6 lm/W
Luminous Efficacy (rated) (Nom)	114 lm/W
Color Rendering Index (Nom)	21
Operating and Electrical	
Lamp Current (Nom)	3 A
Ignition Supply Voltage (Max)	198 V

Re-Ignition Time (Min) (Max)		1 s
Ignition Time (Max)		5 s
Voltage (Max)		120 V
Voltage (Min)		90 V
Voltage (Nom)		100 V
Mechanical and Housing		
Bulb Finish		Clear (CL)
Cap-Base Information		Nic/Brass
Bulb Material		Hard Glass
Approval and Application		
Mercury (Hg) Content (Max)		63.8 mg
Luminaire Design Requirements		
Bulb Temperature (Max)		400 °C
Cap-Base Temperature (Max)		210 °C
Product Data		
Order product name		C250S50/2 12PK


Ceramalux Instant Restrike

EAN/UPC - Product	046677377175
Order code	377176
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12

Material Nr. (12NC)	928601145501
Net Weight (Piece)	0.001 kg

Dimensional drawing

Product	D	C
C250S50/2 12PK	2.25 in	9.75 in



HPS 2 250W E39 ED18 U

