

Philips ALTO II Technology

Philips T8 Fluorescent Lamps featuring ALTO II Technology

Better for your business, better for the environment



ALTO lamps with green endcaps have become synonymous with environmental responsibility and low mercury. Since the launch of ALTO Lamp Technology in 1995, 2.0 billion Philips fluorescent lamps with ALTO Lamp Technology have been produced with over 20 tons less mercury than previous non-ALTO lamps¹.

Philips launched ALTO II Technology in 2007. ALTO II Technology has 50% less mercury than prior T8 lamps featuring ALTO Technology, making these lamps the most sustainable linear fluorescents available. Best of all, these lamps offer the same performance levels as ALTO lamps (life, energy, and light output).

Philips T8 Lamp Limited Warranty Periods²

Philips Lamp	Instant Start Limited Warranty (3hr/12hr starts)	Programmed Start Limited Warranty (3hr/12hr starts)
T8 700, HL700 and 800 Series	30/30 Months	30/36 Months
Advantage T8 32W High Lumen	30/30 Months	36/36 Months
Plus T8 32W	36/42 Months	42/48 Months
T8 Energy Advantage and Value Energy Advantage 25W	36/42 Months	48/54 Months
Energy Advantage T8 25W XLL, 28W XLL & 32W XLL	42/48 Months	48/60 Months
32W Twice the Life T8 (2XL)	42/48 Months	48/72 Months
Energy Advantage T8 25W 2XL & 28W 2XL Twice the Life (2XL)	48/60 Months	60/84 Months

Did you know?

- ALTO II T8 lamps have warranty periods ranging from 2½–7 years³
- ALTO II T8 lamps require no burn in before dimming
- ALTO II T8 lamps can contribute to LEED-EB certification. For more information, go to www.usgbc.org

Philips T8 Lamp Family—Life ratings

Philips Lamp	Instant Start ⁴		Programmed Start ⁵	
	3 hours	12 hours	3 hours	12 hours
T8 700, HL700 & 800 Series	24,000	30,000	30,000	36,000
Advantage T8 32W High Lumen	24,000	30,000	30,000	36,000
Plus T8 32W	30,000	36,000	36,000	44,000
T8 Energy Advantage & Value Energy Advantage 25W and 28W	32,000	38,000	38,000	44,000
Energy Advantage T8 25W XLL, 28W XLL & 32W Extra Long Life (XLL)	40,000	46,000	46,000	52,000
32W Twice the Life T8 (2XL)	46,000	52,000	60,000	70,000
Energy Advantage T8 25W 2XL & 28W 2XL Twice the Life (2XL)	60,000	68,000	80,000	90,000

1) [1994 industry average (22.8mg)—PLC average (4.0mg)] × 2 billion lamps. Convert to pounds by dividing by 454. Convert to tons by dividing by 2000.

2) Conditions apply—Based on maximum annual burn hours of 5110. Please contact Philips for warranty conditions for use of other equipment, including sensors.

3) Warranty Periods: 700 & 800 Series T8—30 months; Energy Advantage T8—36 months; PLUS T8—36 months; and Advantage T8—36 months; Extra Long Life T8—48 months; Energy Advantage Extra Long Life T8—48 months.

4) Average life under engineering data on instant start ballast with lamps turned off and restarted once every 3 or 12 operating hours as indicated.

5) Average life under engineering data on programmed start ballast with lamps turned off and restarted once every 3 or 12 operating hours as noted.

Fluorescent Lamps

Advantage T8 Lamps

Watts	Product Number	Symbols, Footnotes	Ordering Code	Pkg. Qty.	Description	Nom. Length (In.)	Rated Average Life 3 Hr. Start (202)	Rated Average Life 12 Hr. Start (241)	Approx. Initial Lumens (203,204)	Design Lumens (208)	CRI
-------	----------------	--------------------	---------------	-----------	-------------	-------------------	--------------------------------------	---------------------------------------	----------------------------------	---------------------	-----

Advantage T8 High Lumen Fluorescent Lamps

T8 Medium Bipin Featuring ALTO II Technology

17	28130-3	Ⓢ ●	F17T8/ADV830/ALTO	30	Advantage 830, 3000K	24	24,000	30,000	1500	1450	85
	28131-1	Ⓢ ●	F17T8/ADV835/ALTO	30	Advantage 835, 3500K	24	24,000	30,000	1500	1450	84
	28132-9	Ⓢ ●	F17T8/ADV841/ALTO	30	Advantage 841, 4100K	24	24,000	30,000	1500	1450	82
25	28140-2	Ⓢ ●	F25T8/ADV835/ALTO	30	Advantage 835, 3500K	36	24,000	30,000	2380	2300	84
	28142-8	Ⓢ ●	F25T8/ADV841/ALTO	30	Advantage 841, 4100K	36	24,000	30,000	2380	2300	82
32	28080-0	Ⓢ ●	F32T8/ADV830/ALTO	30	Advantage 830, 3000K	48	24,000	30,000	3100	3000	85
	28081-8	Ⓢ ●	F32T8/ADV835/ALTO	30	Advantage 835, 3500K	48	24,000	30,000	3100	3000	84
	28085-9	Ⓢ ●	F32T8/ADV841/ALTO	30	Advantage 841, 4100K	48	24,000	30,000	3100	3000	82
	28089-1	Ⓢ ●	F32T8/ADV850/ALTO	30	Advantage 850, 5000K	48	24,000	30,000	3000	2910	82

For the most current product information, go to the e-catalog on www.philips.com
Fluorescent symbols and footnotes located on page 42

Energy Savings: Two Lamp vs. Two Lamp System

Electronic Ballast	Ballast Factor	No. of Lamps	Lamp Watts	Standard T8 Lumens	Advantage T8 Lumens	System Watts	Savings
Standard T8	0.87	2	32	2850	—	58	—
Reduced Light Output T8	0.75	2	32	—	3100	51	\$2.80/yr

Combine Advantage T8 lamps with reduced light output electronic ballasts, with these results:

- Saves 7 system watts vs. standard T8 system
- Saves \$2.80 per fixture per year
- Energy savings based on 4000 hrs/yr @ \$.10 kw/hr

Energy Savings: Two Lamp vs. Three Lamp System

Electronic Ballast	Ballast Factor	No. of Lamps	Lamp Watts	Standard T8 Lumens	Advantage T8 Lumens	System Watts	Savings
Standard T8	0.87	3	32	2850	—	88	—
Increased Light Output T8	1.20	2	32	—	3100	78	\$4.00/yr

Combine advantage T8 lamps with increased light output ballasts. A two lamp advantage T8 system vs. a three lamp standard T8 system will:

- Save 10 system watts
- Save \$4.00 per fixture per year
- Save energy based on 4000 hrs/yr @ \$.10 kw/hr
- Reduce lighting installation costs (lamps, ballasts, fixtures and labor)
- Operate on ballast with ballast factors up to 1.32 with warranty intact



T8 Medium Bipin

Rated Average Life

- Philips Advantage Instant Start Ballast
- Philips Advantage Programmed Start Ballast

