



Ceramalux Non-ALTO

SON 150W E26 BD54 CL SLV/12

Philips Ceramalux lamps provide efficient lighting solutions for industrial applications, warehouses, post top applications and parking lots.

Product data

General Information			
Cap-Base	E26 [Single Contact Medium Screw]	Ignition Supply Voltage (Max)	110 V
Operating Position	UNIVERSAL [Any or Universal (U)]	Re-Ignition Time (Min) (Max)	2 min
Main Application	General Lighting (G)	Ignition Time (Max)	5 s
ANSI Code HID	S55	Voltage (Max)	62 V
Footnotes HID 1	For use in fixtures which do not redirect a substantial portion of the energy toward the arc tube; otherwise very early failure is anticipated. (376)	Voltage (Min)	48 V
		Voltage (Nom)	55 V
Light Technical		Mechanical and Housing	
Luminous Flux (Rated) (Min)	15300 lm	Bulb Finish	Clear
Luminous Flux (Rated) (Nom)	16500 lm	Cap-Base Information	Brass Cap
Lumen Maintenance 10000 h (Nom)	75 %	Bulb Material	Hard Glass
Design Mean Lumens	14400 lm		
Chromaticity Coordinate X (Nom)	514	Approval and Application	
Chromaticity Coordinate Y (Nom)	424	Picogram Per Lumen Hour	46.6 pg/lm.h
Correlated Color Temperature (Nom)	2100 K	Mercury (Hg) Content (Max)	17 mg
Luminous Efficacy (Rated) (Min)	102 lm/W		
Luminous Efficacy (rated) (Nom)	110 lm/W	UV	
Color Rendering Index (Max)	25	Pet (Niosh) (Nom)	89 h/500lx
Color Rendering Index (Nom)	17	Damage Factor D/fc (Nom)	0.08
Operating and Electrical			
Lamp Current (Nom)	3.2 A	Luminaire Design Requirements	
		Bulb Temperature (Max)	400 °C
		Cap-Base Temperature (Max)	190 °C


Ceramalux Non-ALTO

Product Data	
Order product name	SON 150W E26 BD54 CL SLV/12
EAN/UPC - Product	046677303471
Order code	928601147404
Numerator - Quantity Per Pack	1

Numerator - Packs per outer box	12
Material Nr. (12NC)	928601147404
Net Weight (Piece)	0.100 kg

Dimensional drawing

Product	D	C (max)
SON 150W E26 BD54 CL SLV/12	2.125 in	5.438 in



HPS R 150W E26 BD17 U

