



Family

**Catalog Number:** CUSG-29B.31  
**Product ID:** 7TAA292490R0003  
**UPC Number:** 78620995446  
**EAN Number:** 07630030224218  
**Status:** Active

Coarse Profile Medium Wall Very Flexible Black Conduit, (CUS) Material - Polyamide 6, Conduit Size NW - 29, 31 Meters

- Cost-effective
- Very good flexibility
- Good impact strength, also at low temperatures and dry conditions
- Self-extinguishing, free of halogens and cadmium
- Renewable Energy
- Electrical Installations

#### North American Specifications (UNSPSC)

|             |                             |
|-------------|-----------------------------|
| UNSPSC      | 39131706 Electrical conduit |
| IGCC        | 5535 Electrical conduit     |
| Brand Name  | PMA                         |
| Type        | Medium Wall Conduit         |
| Application | Machine                     |
| Standard    | cULus                       |
| Trade Size  | NW29                        |
| Length      | 31 Meters                   |
| Flexibility | Very Flexible               |
| Material    | Polyamide/Nylon 6           |
| Color       | Black                       |

#### European Specifications (ETIM)

|                                            |                                  |
|--------------------------------------------|----------------------------------|
| ETIM                                       | EC001175 Corrugated plastic hose |
| Nominal diameter                           | 32mm                             |
| Nominal size in inch                       | 1 inch                           |
| Outer diameter                             | 34.5mm                           |
| Inner diameter                             | 27.6mm                           |
| Material                                   | Polyamide 6                      |
| Compressive strength                       | 150N                             |
| Operating temperature                      | -40 - +105°C                     |
| Fire resistance in accordance with UL94    | V2                               |
| UV resistant                               | Y                                |
| Colour                                     | Black                            |
| Sheathing material                         | Not sheathed                     |
| Bending strength                           | Flexible                         |
| Lengthwise slotted                         | N                                |
| Closable (two-part)                        | N                                |
| Halogen free                               | Y                                |
| Approved according to DIN EN 61386-23      | N                                |
| Approved according to UR                   | Y                                |
| Approved according to CSA                  | N                                |
| Approved according to LUL/British Standard | N                                |
| Approved according to Lloyd's Register TA  | N                                |
| Approved according to UTAC                 | N                                |
| Approved according to DIN 5510             | N                                |

Approved according to NF F 16-101      N

#### Packaging

|                           |                      |
|---------------------------|----------------------|
| Inner Quantity            | 1                    |
| Outer Quantity            | 8                    |
| Outer Dimensions (inches) | 47.244x31.496x29.528 |
| Weight Uom                | 0.01 lbs. Each       |

#### Documents / Support Tools

Technical Data Sheet CA      Available on Website

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)