



Family

Catalog Number: **LLPF-12A.50**
Product ID: 7TAA292030R0039
UPC Number: 78620995792
EAN Number: 07630030249686
Status: Active

Fine Profile Medium-Wall Flexible Black Conduit, (LLPF) Material - Polyamide 6, Conduit Size NW - 12, 50 Meters

- Very good flammability characteristics
- Self-extinguishing
- Free from halogens and cadmium
- Good flexibility
- Good pressure resistance
- Good impact resistance
- Good weather resistance
- Renewable Energy

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5535 Electrical conduit
Brand Name	PMA
Type	Medium Wall Conduit
Application	Machine
Trade Size	NW12
Outside Diameter	0.62 Inch
Inside Diameter	0.47 Inch
Length	50 m
Flexibility	Medium Flexibility
Material	Polyamide/Nylon 6
Color	Black

European Specifications (ETIM)

ETIM	EC001175 Corrugated plastic hose
Nominal diameter	16mm
Outer diameter	15.8mm
Inner diameter	12mm
Material	Polyamide 6
Compressive strength	175N
Operating temperature	-40 - +105°C
Fire resistance in accordance with UL94	V0
UV resistant	Y
Colour	Black
Sheathing material	Not sheathed
Bending strength	Flexible
Lengthwise slotted	N
Closable (two-part)	N
Halogen free	Y
Approved according to DIN EN 61386-23	N
Approved according to UR	N
Approved according to CSA	N
Approved according to LUL/British Standard	N
	Y

Approved according to Lloyd's Register
TA

Approved according to UTAC	N
Approved according to DIN 5510	N
Approved according to NF F 16-101	N

Packaging

Inner Quantity	1
Outer Quantity	20
Outer Dimensions (inches)	47.244x31.496x29.528
Weight Uom	0.28 lbs. Each

Documents / Support Tools

Video US Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com