

6" INCANDESCENT

HIGH WATTAGE IC HOUSINGS & TRIMS

For insulated ceilings. IC trims may be used as non-IC trims with same wattages. 7-3/4" outside diameter (OD), except where indicated.

New Construction or Top Accessible Ceilings Air-Tight IC



P821-AT

Ceiling opening: 6-7/8" dia.
Plaster frame: 8-3/8" x 13"
Recessed depth: 7-5/8"
Pryouts 1/2" and 3/4"

P821-AT

- Allows for high wattage in insulated ceilings up to 150w
- Meets Washington State Energy Code requirements
- Can be installed in ceilings from 1/2" to 2-1/2" thick
- UL and CUL listed for damp locations and through wiring
- Socket mounts to trim for consistent lamp position
- Spans 24" T-bar spacing
- Integral Romex clamp
- Integral nailer and T-bar mounting clamp
- Rated for 8 #12 90° conductors (4 in/4 out)
- US Patent #5758959, 5857766, 6004001

Open Splay



P8072-28 White
Lamp: 85w BR30, 75w PAR 30 Long Neck, 75w A19

Drop Opal Shower

Wet location listed



P8007-60 White
Metal flange, OD: 8-1/4" dia.
Lamp: 75w A19, 75w PAR 30

Step Baffle



P8075-28 White
P8075-31 Black
Lamp: 85w BR30, 75w PAR30 Long Neck, 75w A19

Step Baffle



P8082-28 White
P8082-31 Black
OD: 8-3/4"
Lamp: 120w BR40, 150w PAR 38

Eyeball

Rotates 358°, tilts 30° max.



P8076-09 Brushed Nickel
P8076-20 Antique Bronze
P8076-28 White
Lamp: 85w BR30, 75w PAR 30

Open



P8074-28 White
OD: 8-3/4"
Lamp: 120w BR40, 150w PAR 38

Drop Opal Shower

Wet location listed



P8009-60 White glass
Non-metallic flange
Lamp: 60w A19, 75w PAR 30

Step Baffle



P8066-20 Antique Bronze
Lamp: 120w BR40, 150w PAR 38, 100w A19

Cones



P8053-31 Black Alzak®
Black Flange
Lamp: 150w PAR 38, 120w BR 40, 100w A19

Baffled Eyeball

Rotates 358°, tilts 30° max.



P8079-28 White Baffle
P8079-31 Black Baffle and Black Eyeball
Lamp: 85w BR30, 75w PAR 30

Fresnel

Wet location listed



P8062-28 White
Metal flange
Lamp: 40w A19

Open Shower Trims

Wet location listed



P8072WL-28 White
Metal flange
Lamp: 50w PAR 30 Long Neck
P8074WL-28 White
OD: 8-3/4"
Lamp: 75w PAR 38*

Step Baffle



P8066-09 Brushed Nickel*
P8066-31 Black
Lamp: 120w BR40, 150w PAR 38, 100w A19
*Unpainted flange

Cones



P8068-22A Gold Alzak®
P8068-21A Clear Alzak®
P8068-28 White
White Flange
Lamp: 120w BR 40, 150w PAR 38, 100w A19

Baffled Mini Eyeball

Rotates 358°, tilts 30° max.



P8077-28 White Baffle
Lamp: 75w R20, PAR 16, PAR 20

Albalite

Wet location listed



P8060-28 White
Metal Flange
Lamp: 40w A19

Dome Shower

Wet location listed



P8025-60 White
Polycarbonate
8-3/4" outside diameter
Lamp: 60w A19

Step Baffle



P8066-28 White
Lamp: 120w BR40, 150w PAR 38, 100w A19

Wall Washer



P8052-28 White Baffle
Lamp: 40w A19

Regressed Mini Eyeball

Rotates 358°, tilts 30° max.



P8078-28 White
Lamp: 75w R 20, PAR 16, PAR 20

Fresnel

Wet location listed



P8011-60
Non-metallic flange
Lamp: 75w PAR30 Short Neck

Lamp wattages shown are maximum.

For accessories see page 680.

* WL trims require use with outdoor rated PAR lamps