

T8

8.9T8/MAS/48-850/IF16/P/DIM 10/1

Our TLEDs are available in InstantFit (Type A / Type C) or MainsFit (Ballast bypass / Type B) versions. The InstantFit lamps work on a broad variety of ballasts and LED drivers. Only InstantFit has over 15,000 lamp & ballast combinations delivering even light output, energy savings and a long lifetime. Our MainsFit products feature a double-ended design, simplifying installation while a proprietary safety circuit minimizes a shock risk. Lamp sizes range from 2-foot to 8-foot and U-bend with a variety of lumen outputs.

Product data


General Information		Power (Rated) (Nom)		8.9 W
Base	G13 [Medium Bi-Pin Fluorescent]	Lamp Current (Max)	300 mA	
EU RoHS compliant	Yes	Lamp Current (Min)	90 mA	
Nominal Lifetime (Nom)	70000 h	Starting Time (Nom)	0.5 s	
Switching Cycle	50000X	Warm Up Time to 60% Light (Nom)	0.5 s	
Technical Type	8.9-32W	UL Type	Type A - works on ballast	
Light Technical		Power Factor (Nom)	0.9	
Color Code	850 [CCT of 5000K]	Voltage (Nom)	120-277, 347 V	
Beam Angle (Nom)	180 °	Temperature		
Initial lumen (Nom)	1600 lm	T-Ambient (Max)	45 °C	
Color Designation	Daylight	T-Ambient (Min)	-20 °C	
Correlated Color Temperature (Nom)	5000 K	T-Storage (Max)	65 °C	
Luminous Efficacy (rated) (Nom)	179.00 lm/W	T-Storage (Min)	-40 °C	
Color Consistency	<5	T-Case Maximum (Nom)	50 °C	
Color Rendering Index (Nom)	80	Controls and Dimming		
LLMF At End Of Nominal Lifetime (Nom)	70 %	Dimmable	Yes	
Operating and Electrical				
Input Frequency	20K to 120K Hz			

T8

Mechanical and Housing	
Bulb Finish	Frosted
Bulb Material	Plastic
Product Length	48 in
Bulb Shape	Tube, double-ended
Approval and Application	
Energy Saving Product	Yes
Approbation Marks	RoHS compliance UL certificate DLC compliance
Energy Consumption kWh/1000 h	- kWh

Product Data	
Order product name	8.9T8/MAS/48-850/IF16/P/DIM 10/1
EAN/UPC - Product	046677565619
Order code	565614
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929003025604
Net Weight (Piece)	0.220 kg
Model Number	9290030256


Dimensional drawing




TLED T8 HFV 8.9-32W 1600lm 5000K G13

Product	D1	D2	A1	A2	A3
8.9T8/MAS/48-850/IF16/P/DIM 10/1	25.7 mm	26.3 mm	1198.1 mm	1205.2 mm	1212.3 mm

Photometric data




LEDtube MAS 8,9W G13 1600lm 850




LEDtube MAS 8,9W G13 1500lm

Photometric data




LEDtube MAS 8,9W G13 1600lm 850


Lifetime




LEDtube MAS 8,9W 70K LumenVsTc



LEDtube_70K-LED




LEDtube_70K_LifetimeVsTc-LED



LEDtube_70K_FailureRate-LED

Lifetime



LEDtube_70K-LMP

