



Cylinders are a complete design solution. They are available in various sizes, mounting options, colors and beam angles, and suitable for indoor/outdoor use.

Color: Matte white

Weight: 8.1 lbs

Project:

Type:

Prepared By:

Date:

Driver Info

Type	Constant Current
120V	0.24A
208V	0.14A
240V	0.12A
277V	0.12A
Input Watts	27.9W

LED Info

Watts	26W
Color Temp	3500K (Warm Neutral)
Color Accuracy	92 CRI
R9	58
L70 Lifespan	50,000 Hours
Lumens	2,345
Efficacy	84.1 lm/W

Technical Specifications

Compliance

UL Listed:

Suitable for wet locations

IESNA LM-79 & IESNA LM-80 Testing:

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

Electrical

Driver:

Constant Current, Class 2, 120-277V, 50/60 Hz, 120V: 0.24A, 208V: 0.14A, 240V: 0.12A, 277V: 0.12A

Dimming Driver:

0 - 10V (at 120-277V), TRIAC and ELV (at 120V only)

THD:

13.1% at 120V, 18.3% at 277V

Power Factor:

98.5% at 120V, 90.8% at 277V

Optical

Optics:

80°

Performance

Lifespan:

50,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

LED Characteristics

LEDs:

Long-life, high-efficacy, surface-mount LEDs

Color Stability:

LED color temperature is warranted to shift no more than 200K in color temperature over a 5-year period

Construction

Cold Weather Starting:

The minimum starting temperature is -30°C (-22°F)

Maximum Ambient Temperature:

Suitable for use in up to 40°C (104°F)

Lens:

Solite Glass Lens and Microprismatic Diffusion Lens

Reflector:

Vacuum-metalized polycarbonate

Technical Specifications (continued)

Construction

Housing:

Extruded aluminum

Mounting:

Wall indirect light only

Gaskets:

High-temperature silicone

Green Technology:

Mercury and UV free. RoHS-compliant components.

Finish:

Formulated for high durability and long-lasting color

Other


Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Dimensions



Features

Sleek, contemporary, architectural-grade design
Universal dimming driver (TRIAC, ELV and 0-10V)
50,000-Hour LED lifespan

Ordering Matrix

Family	Size	Mounting		Wattage		Optic	CRI/Color Temp		Finish
CDLED	6	WU	-	26W	-	80D	935	-	W
	2 = 2"	WD = Wall Direct (Downlight) Only		10W = 10W		20D = 20°	927 = 90 CRI, 2700K		W = Matte
	4 = 4"	WU = Wall Indirect (Uplight) Only		20W = 20W		30D = 30°	930 = 90 CRI, 3000K		White
	6 = 6"	W = Wall Direct/Indirect (Downlight/Uplight)		26W = 26W		40D = 40°	935 = 90 CRI, 3500K		K = Matte Black
		S = Surface (Ceiling Mount)		40W = 40W		50D = 50°	940 = 90 CRI, 4000K		S = Matte Silver
		PC = Pendant Cord 48" Standard				80D = 80°	950 = 90 CRI, 5000K		Z = Bronze
		PS = Pendant Stem				WW = Wall Wash			