


**RIGID REDUCING BUSHINGS - STEEL****Reducing Bushings Steel****B34**

Catalog #: 1143

APPLICATIONS

For use with threaded rigid/IMC conduit to reduce the size of a female hub to accommodate a smaller size of conduit or male threaded hub
Rugged steel construction insures mechanical protection of the raceway

PRODUCT FEATURES

Zinc electro plated for corrosion protection
N/A

CULUS

UL Listed E195969

COMPLIANCES

MSDS
www.hubbell-rtb.com/certifications/Hubbell-RACO_MSDS_for_WP_Boxes_and_Fittings,January_2015.pdf

GENERAL PRODUCT INFORMATION

Trade Size: 1 in. to 1/2 in.

DRAWING DIMENSIONS

Dimension A: 1-9/32 in.
Thread Spec. A: 1 in. - 11-1/2 NPS
Dimension B: 39/64 in.
Thread Spec. B: 1/2 in. - 14 NPS
Dimension C: 5/8 in.

PACKAGING

Package Type: Carton
Ship Carton Qty.: 50
Product UPC-A Labeled: No
Weight (Lbs. Per/C): 12.10
Ship Carton Length (in.): 6.25
Ship Carton Width (in.): 4.50
Ship Carton Height (in.): 4.25
Ctn Weight (Lbs.): 6.05
UPC Number: 050169011430
I2of5: 50050169011435