


**EMT SET SCREW COUPLINGS**

Set Screw Couplings, Steel

B04

Catalog #: 2025

APPLICATIONS

For use in dry locations to couple two ends of EMT conduit. RACO set screw couplings provide concrete-tight connections when taped. RACO set screw couplings are suitable for applications above 600V.

PRODUCT FEATURES

All steel construction ensures mechanical protection for the raceway
Tri-head screws (1/2 in. to 2 in. trade sizes) may be installed using a slotted, Phillips, or Robertson head screwdriver
2-1/2 in. to 4 in. trade sizes are also UL listed for use on Rigid/IMC conduit, allowing for design and installation flexibility
All components are zinc electroplated for corrosion protection
UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code, and packaged in pre-scored tear top cartons for an attractive presentation

UL LISTED

2-1/2" - 4" Standard 514B, File E195969, E195970

CULUS

1/2" - 2" Standard 514B, C22.2 # 18

COMPLIANCES

MSDS
www.hubbell-rtb.com/certifications/Hubbell-RACO_MSDS_for_WP_Boxes_and_Fittings_January_2015.pdf

GENERAL PRODUCT INFORMATION

Trade Size: 1-1/4 in.

DRAWING DIMENSIONS

Dimension A: 3.03 in.
Dimension B: 1.70 in.
Thread Spec. C: 1/4-28UNS

PACKAGING

Package Type: Carton
Std. Pkg.: 5
Ship Carton Qty.: 25
Product UPC-A Labeled: No
Weight (Lbs. Per/C): 44.40
Ship Carton Length (in.): 11.47
Ship Carton Width (in.): 8.91
Ship Carton Height (in.): 6.01
Pallet Qty: 2400
UPC Number: 050169020258