


**EMT SET SCREW COUPLINGS**

Set Screw Couplings, Steel

B04

Catalog #: 2152

APPLICATIONS

For use in dry locations to couple two ends of EMT conduit. RACO set screw couplings provide concrete-tight connections when taped. RACO set screw couplings are suitable for applications above 600V.

For use in dry locations to couple two ends of unthreaded rigid/IMC conduit. RACO set screw couplings provide concrete-tight connections when taped.

PRODUCT FEATURES

All steel construction ensures mechanical protection for the raceway

All steel construction insures mechanical protection for the raceway

Tri-head screws (1/2 in. to 2 in. trade sizes) may be installed using a slotted, Phillips, or Robertson head screwdriver

2-1/2 in. to 4 in. trade sizes are also UL listed for use on EMT or Rigid/IMC conduit, allowing for design and installation flexibility

All components are zinc electroplated for corrosion protection

All components are zinc electroplated for corrosion protection

UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code, and packaged in pre-scored tear top cartons for an attractive presentation

UL LISTED

2-1/2" - 4" Standard 514B, File E195969, E195970
Standard 514B, UL Listed E195969

CULUS

1/2" - 2" Standard 514B, C22.2 # 18

COMPLIANCES

MSDS

www.hubbell-rtb.com/certifications/Hubbell-RACO_MSDS_for_WP_Boxes_and_Fittings_January_2015.pdf

MSDS

www.hubbell-rtb.com/certifications/Hubbell-RACO_MSDS_for_WP_Boxes_and_Fittings_January_2015.pdf

US PATENTS

N/A

GENERAL PRODUCT INFORMATION

Trade Size: 3 in.

DRAWING DIMENSIONS

Dimension A: 4.33 in.
Dimension B: 3.77 in.
Thread Spec. C: 1/4-24UNS

PACKAGING

Package Type: Carton
Ship Carton Qty.: 1
Product UPC-A Labeled: No
Weight (Lbs. Per/C): 184.30
Ship Carton Length (in.): 4.07
Ship Carton Width (in.): 4.07
Ship Carton Height (in.): 5.03
Ctn Weight (Lbs.): 1.84
Pallet Qty: 800
UPC Number: 050169021521