


**EMT COMPRESSION CONNECTORS**

Compression Connectors, Steel

B05

Catalog #: 2903

APPLICATIONS

For use to bond EMT conduit to a box or enclosure.
RACO Compression connectors are suitable for applications above 600V.

PRODUCT FEATURES

1/2 in. to 4 in. connectors provide concrete-tight connections
All steel construction ensures mechanical protection for the raceway
All components are zinc electroplated for corrosion protection
UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code, and packaged in pre-scored tear top cartons for an attractive presentation.

CULUS

Standard 514B, UL Listed E195970, C22.2 No. 1

COMPLIANCES

MSDS
www.hubbell-rtb.com/certifications/Hubbell-RACO_MSDS_for_WP_Boxes_and_Fittings,January_2015.pdf

GENERAL PRODUCT INFORMATION

Sub Class: Uninsulated
Trade Size: 3/4 in.

DRAWING DIMENSIONS

Dimension A: 1.79 in.
Dimension B: .45 in.
Dimension C: 1.38 in.

PACKAGING

Package Type: Carton
Std. Pkg.: 25
Ship Carton Qty.: 250
Product UPC-A Labeled: No
Weight (Lbs. Per/C): 17.40
Ship Carton Length (in.): 20.92
Ship Carton Width (in.): 9.74
Ship Carton Height (in.): 8.06
Ctn Weight (Lbs.): 43.42
UPC Number: 050169029039
I2of5: 50050169029034