

Learn more at www.redlion.net.

Call +1 (717) 767-6511 to speak to a representative.



MODEL DSPSX

Data Station Plus SX

MODEL DSPSX

Data Station Plus SX

- > Multiple protocol Converter
- > Web server provides access to custom web pages, virtual HMI, data and event logger
- > Virtual HMI QVGA size maximum (320x240) provides remote monitoring and control
- > Configured via Crimson 3.0 Windows compatible software
- > Two (2) RS232 and one (1) RS485/422 serial communication ports on board
- > 10/100 Base-T Ethernet port supports multiple protocols
- > USB Port to download the unit's configuration from a PC
- > CompactFlash Socket to increase memory capacity for data-log files and custom web pages
- > FTP server and synchronization for file transfer
- > OPC Server for easy SCADA connectivity using OPCWorx
- > Optional card adds fieldbus connectivity, extra serial ports, etc.



MODEL DSPLE

Data Station Plus LE

MODEL DSPLE

Data Station Plus LE

- > Multiple protocol Converter
- > Configured via Crimson 3.0 Windows compatible software
- > Two (2) RS232 and one (1) RS485/422 serial communication ports on board
- > 10/100 Base-T Ethernet port supports multiple protocols
- > USB Port to download the unit's configuration from a PC
- > CompactFlash Socket for programming only
- > Optional card adds fieldbus connectivity or extra serial ports

MODEL XC

Optional communication card*

XCRS0000 - Isolated serial communication card with one RS232 and one RS422/485

XCPBDP00 - Profibus DP slave communication card

XCDN0000 - DeviceNet slave communication card

XCCN0000 - CanOpen communication card

XCENET00 - Ethernet communication card

XCGSM000 - GSM cellular modem card

*Each DSP can accept one expansion card