

# NT24k®-DR16 Modular Industrial Switch

N-Tron® Networking Series



## Managed Gigabit Industrial Ethernet Switch

The N-Tron® series NT24k®-DR16 is a modular managed switch designed for factory automation, utilities, security surveillance, SCADA and other industrial applications.

The Red Lion N-Tron series NT24k-DR16 managed industrial Ethernet switch features connectivity for up to 16 Gigabit ports and offers a wide range of connectivity options—including 100Base, Gigabit, fiber optic and copper options—in a rugged DIN-rail mountable enclosure. Designed to handle the most demanding environments, the NT24k-DR16 delivers wire-speed throughput and includes expanded shock and vibration tolerances, extreme operating temperature range and two slots to accommodate mix-and-match port modules. N-Ring™ technology restores network communication within ~30ms of fault detection. Robust remote monitoring capabilities make management easy.



### APPLICATIONS

- > Factory Automation
- > Utilities
- > SCADA
- > Security Surveillance
- > Transportation
- > Alternative Energy

### PRODUCT HIGHLIGHTS

- > All Gigabit Modular Design
- > Up to 16 Port Connections
- > High Environmental Specifications
- > N-Ring Advanced Ring Technology
- > Robust Remote Monitoring
- > Smart Plug-and-Play Operation

### IEEE 1588v2 PTP OPTIONS

- Boundary Clock
- Transparent Clock

IEEE 1588v2 applications include

- Coordinated motion control
- Time-stamped data logging
- Time-stamped fault detection

**PTP Models & Upgrade Kit Available**

### FEATURES & BENEFITS

- > Supports up to two of the following port modules:
  - 8-port 10/100/1000BaseT(X) module
  - 8-port 100Base fiber module
  - 8-port 1000Base fiber module
  - 8-port Gigabit SFP module
  - 8-port dual mode SFP module (100Base or 1000Base SFP transceivers)
- > -40°C to 75°C operating temperature
- > Power input selections:
  - Low Voltage: 18-49 VDC
  - High Voltage: 90-264 VAC or 90-300 VDC
- > Onboard temperature sensor
- > ESD and surge protection diodes on all copper ports
- > Auto-sensing 10/100/1000BaseT(X), duplex and MDIX
- > USB configuration port
- > Configurable alarm contact
- > Optional backup/restore configuration device
- > Fully managed features include:
  - SSH/SSL/HTTPS
  - SNMP v1, v2, v3
  - Web browser management
  - Detailed ring map and fault location charting
  - RSTP - 802.1d, 802.1w, 802.1D
  - Trunking and port mirroring
  - 802.1Q tag VLAN and port VLAN
  - IEEE 802.1x with RADIUS remote server authentication
  - DHCP Server, Option 82 relay, Option 61, IP fallback
  - Port Security – MAC address based
  - 802.1p QoS, port QoS and DSCP
  - Event Log/Syslog
  - SNTP (Simple Network Time Protocol)
  - IEEE 1588v2 (PTP) models available
  - Multi-Member N-Ring technology with ~30ms healing
  - N-Link™ redundant ring technology
  - N-View™ monitoring technology
  - EtherNet/IP™ CIP™ messaging

industrial  
networking



EtherNet/IP®

All specifications are subject to change. Consult the company website for more information.

# Managed Gigabit Industrial Ethernet Switch Specifications

## NT24K-FX8 MODULE - 100 MB FIBER TRANSCEIVER CHARACTERISTICS

| Fiber Mode         | MM      | SM      | SM      | SM      |
|--------------------|---------|---------|---------|---------|
| Fiber Length*      | 2km     | 15km    | 40km    | 80km    |
| TX Power Min       | -19 dBm | -15 dBm | -5 dBm  | -5 dBm  |
| RX Sensitivity Max | -31 dBm | -31 dBm | -34 dBm | -34 dBm |
| Wavelength         | 1310 nm | 1310 nm | 1310 nm | 1550 nm |

## NT24K-GX8 MODULE - GIGABIT FIBER TRANSCEIVER CHARACTERISTICS

| Fiber Mode         | MM                                   | SM       | SM      | SM      |
|--------------------|--------------------------------------|----------|---------|---------|
| Fiber Length*      | 550m @ 50/125µm<br>300m @ 62.5/125µm | 10km     | 40km    | 80km    |
| TX Power Min       | -9.5 dBm                             | -9.5 dBm | -5 dBm  | 0 dBm   |
| RX Sensitivity Max | -17 dBm                              | -20 dBm  | -23 dBm | -24 dBm |
| Wavelength         | 850 nm                               | 1310 nm  | 1310 nm | 1550 nm |
| Laser Type         | VCSEL                                | FP       | DFB     | DFB     |

## NT24K-SFP-DM8 MODULE - SFP 100BASE FIBER TRANSCEIVER CHARACTERISTICS

| Fiber Mode         | MM      | SM      | SM      | SM      |
|--------------------|---------|---------|---------|---------|
| Fiber Length*      | 2km     | 15km    | 40km    | 80km    |
| TX Power Min       | -19 dBm | -15 dBm | -5 dBm  | -5 dBm  |
| RX Sensitivity Max | -31 dBm | -34 dBm | -34 dBm | -34 dBm |
| Wavelength         | 1310 nm | 1310 nm | 1310 nm | 1550 nm |
| Laser Type         | FP      | FP      | FP      | DFB     |

## NT24K-SFP-DM8 OR NT24K-SFP8 MODULES- SFP GIGABIT FIBER TRANSCEIVER CHARACTERISTICS

| Fiber Mode         | MM                                   | SM       | SM      | SM      |
|--------------------|--------------------------------------|----------|---------|---------|
| Fiber Length*      | 550m @ 50/125µm<br>275m @ 62.5/125µm | 10km     | 40km    | 80km    |
| TX Power Min       | -9.5 dBm                             | -9.5 dBm | -2 dBm  | 0 dBm   |
| RX Sensitivity Max | -17 dBm                              | -20 dBm  | -22 dBm | -24 dBm |
| Wavelength         | 850 nm                               | 1310 nm  | 1310 nm | 1550 nm |
| Laser Type         | VCSEL                                | FP       | DFB     | DFB     |

\* Fiber Length distances represent typical performance.  
Link budgets should be evaluated based on specific application conditions.

## ORDERING GUIDE

| PART NUMBER      | DESCRIPTION                                                                                                                        |
|------------------|------------------------------------------------------------------------------------------------------------------------------------|
| NT24K-DR16-DC    | Managed Industrial Ethernet Switch; modular DIN rail design with 2 expansion slots; redundant 18-49VDC power input                 |
| NT24K-DR16-DC-PT | Managed Industrial Ethernet Switch; modular DIN rail design with 2 expansion slots; redundant 18-49VDC power input PTP Enabled     |
| NT24K-DR16-AC    | Managed Industrial Ethernet Switch; modular DIN rail design with 2 expansion slots; 90-264VAC / 90-300VDC power inputs             |
| NT24K-DR16-AC-PT | Managed Industrial Ethernet Switch; modular DIN rail design with 2 expansion slots; 90-264VAC / 90-300VDC power inputs PTP Enabled |
| NT24K-FP         | Filler panel (required to fill vacant module slots)                                                                                |
| NTCD-CFG         | Configuration recovery device                                                                                                      |
| NTPC-AC-US       | AC power cord                                                                                                                      |
| NTPS-24-3        | DIN rail power supply 3.0 Amp@24 VDC                                                                                               |
| NT24K-DR-PMK     | NT24k DR panel mount kit                                                                                                           |
| NT24K-KIT-PTP    | NT24k Upgrade License to Enable IEEE 1588/PTP on Non-PT NT24k Switches                                                             |

## PORT MODULES & TRANSCEIVERS

|                  |                                                                                                      |
|------------------|------------------------------------------------------------------------------------------------------|
| NT24K-TX8        | 8-port 10/100/1000BaseT module                                                                       |
| NT24K-FX8-XX     | Slide-in module with 8 100BaseFX multimode fiber ports, 2km (SC or ST)                               |
| NT24K-FXE8-XX-YY | Slide-in module with 8 100BaseFX singlemode fiber ports (SC or ST)                                   |
| NT24K-GX8-SC     | Slide-in module with 8 1000BaseFX multimode fiber ports, 550m (SC)                                   |
| NT24K-GXE8-SC-ZZ | Slide-in module with 8 1000BaseFX singlemode fiber ports (SC)                                        |
| NT24K-SFP8       | Slide-in module with 8 SFP expansion slots; supports 1000Base SFP transceivers*                      |
| NT24K-SFP-DM8    | Slide-in module with 8 dual mode SFP expansion slots; supports 100Base or 1000Base SFP transceivers* |
| NTSFP-FX         | 100BaseFX multimode fiber SFP pluggable mini-GBIC transceiver (LC style connector, 2km)**            |
| NTSFP-FXE-YY     | 100BaseFX singlemode fiber SFP pluggable mini-GBIC transceiver (LC style connector)**                |
| NTSFP-TX         | 1000BaseT copper SFP pluggable mini-GBIC transceiver                                                 |
| NTSFP-SX         | 1000BaseSX multimode fiber SFP pluggable mini-GBIC transceiver                                       |
| NTSFP-LX-ZZ      | 1000BaseLX singlemode fiber SFP pluggable mini-GBIC transceiver                                      |

Where: XX = ST or SC connector (ST not available on some GX modules); YY = 15, 40, or 80 for FX singlemode, blank for multimode; ZZ = 10, 40, or 80 for GX singlemode; \*SFP transceivers sold separately; \*\*For use with SFP DM8 module only



[www.redlion.net](http://www.redlion.net)

**Connect. Monitor. Control.**

**Americas**  
sales@redlion.net

**Asia-Pacific**  
asia@redlion.net

**Europe  
Middle East  
Africa**  
europe@redlion.net

**+1 (717) 767-6511**

As the global experts in communication, monitoring and control for industrial automation and networking, Red Lion has been delivering innovative solutions for over forty years. Our automation, Ethernet and cellular M2M technology enables companies worldwide to gain real-time data visibility that drives productivity. Product brands include Red Lion, N-Tron and Sixnet. With headquarters in York, Pennsylvania, the company has offices across the Americas, Asia-Pacific and Europe. Red Lion is part of Spectris plc, the productivity-enhancing instrumentation and controls company. For more information, please visit [www.redlion.net](http://www.redlion.net).

ADLD0332 071718 © 2018 Red Lion Controls, Inc. All rights reserved. Red Lion, the Red Lion logo, N-Tron and Sixnet are registered trademarks of Red Lion Controls, Inc. All other company and product names are trademarks of their respective owners.