

SIMATIC DP, ELECTRONIC MODULE 2 AO U HIGH FEATURE
FOR ET 200S, 15 MM WIDE, CYCLE TIME PER MODULE: 0.5MS,
+/-10V; 15 BIT + SIGN, 1 .. 5V; 15 BIT, OPERATIONAL LIMITS +/-
0.07% WITH LED SF (GROUP FAULT)



Supply voltage

Load voltage L+

- Rated value (DC) 24 V
- Reverse polarity protection Yes

Input current

- from load voltage L+ (without load), max. 80 mA
- from backplane bus 3.3 V DC, max. 10 mA

Power loss

- Power loss, max. 1.2 W

Address area

Address space per module

- Address space per module, max. 4 byte

Analog outputs

- Number of analog outputs 2
- Voltage output, short-circuit protection Yes
- Voltage output, short-circuit current, max. 25 mA
- Cycle time (all channels) max. 0.5 ms; At max. 0.5 μ F

Output ranges, voltage	
• 1 V to 5 V	Yes
• -5 V to +5 V	Yes
• -10 V to +10 V	Yes
Connection of actuators	
• for voltage output two-wire connection	Yes
• for voltage output four-wire connection	Yes
Load impedance (in rated range of output)	
• with voltage outputs, min.	1 k Ω
• with voltage outputs, capacitive load, max.	0.5 μ F
Destruction limits against externally applied voltages and currents	
• Voltages at the outputs towards MANA	15 V; max. 15 V continuous; 75 V for max. 1 s (mark to space ratio 1:20)
Cable length	
• shielded, max.	200 m; 100m if Twa < 2ms
Analog value generation for the outputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit; 15 bit + sign
Settling time	
• for resistive load	0.2 ms
• for capacitive load	0.5 ms; At max. 0.5 μ F
• for inductive load	0.5 ms
Errors/accuracies	
Output ripple (relative to output range, bandwidth 0 to 50 kHz), (+/-)	0.02 %
Linearity error (relative to output range), (+/-)	0.01 %
Crosstalk between the outputs, min.	60 dB
Repeat accuracy in steady state at 25 °C (relative to output range), (+/-)	0.01 %
Operational error limit in overall temperature range	
• Voltage, relative to output range, (+/-)	0.1 %
Basic error limit (operational limit at 25 °C)	
• Voltage, relative to output range, (+/-)	0.05 %
Isochronous mode	
Isochronous operation (application synchronized up to terminal)	Yes
Interrupts/diagnostics/status information	
Substitute values connectable	Yes
Diagnostic messages	
• Diagnostic information readable	Yes

• Short-circuit	Yes
• Group error	Yes
Diagnostics indication LED	
• Group error SF (red)	Yes

Parameter	
Remark	7 byte
Diagnostics short-circuit	Disable / enable
Output type/range	deactivated / 1 to 5 V / ± 10 V / ± 5 V
Group diagnostics	Disable / enable
Response to CPU/master STOP	Output current and de-energized/substitute a value/keep last value

Potential separation	
Potential separation analog outputs	
• between the channels	No
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	Yes

Permissible potential difference	
between MANA and M internally (UISO)	75 V DC/60 V AC

Isolation	
Isolation tested with	500 V DC

Dimensions	
Width	15 mm
Height	81 mm
Depth	52 mm

Weights	
Weight, approx.	40 g

last modified: 09/15/2017