

SIMATIC S7-300, DIGITAL INPUT SM 321, OPTICALLY ISOLATED,
32 DI, 120V AC, 1 X 40 PIN



Figure similar

Supply voltage	
Load voltage L1	
• Rated value (AC)	120 V
Input current	
from backplane bus 5 V DC, max.	16 mA
Power loss	
Power loss, typ.	4 W
Digital inputs	
Number of digital inputs	32
Input characteristic curve in accordance with IEC 61131, type 2	Yes
Number of simultaneously controllable inputs	
horizontal installation	
— up to 40 °C, max.	32
— up to 60 °C, max.	24
vertical installation	
— up to 40 °C, max.	32
Input voltage	

• Type of input voltage • Rated value (AC) • for signal "0" • for signal "1" • Frequency range	AC 120 V 0 to 20V 74 to 132V 47 ... 63 Hz
Input current	
• for signal "1", typ.	21 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	No
— at "0" to "1", max.	15 ms
Cable length	
• shielded, max. • unshielded, max.	1 000 m 600 m
Encoder	
Connectable encoders	
• 2-wire sensor — permissible quiescent current (2-wire sensor), max.	Yes 4 mA
Isochronous mode	
Isochronous operation (application synchronized up to terminal)	No
Interrupts/diagnostics/status information	
Alarms	
• Diagnostic alarm • Hardware interrupt	No No
Diagnostic messages	
• Diagnostic functions	No
Diagnostics indication LED	
• Group error SF (red) • Status indicator digital input (green)	No Yes; per channel
Potential separation	
Potential separation digital inputs	
• between the channels • between the channels, in groups of • between the channels and backplane bus	No 8 Yes; Optocoupler
Isolation	
Isolation tested with	2500 V DC
Connection method	
required front connector	40-pin

Dimensions	
Width	40 mm
Height	125 mm
Depth	120 mm
Weights	
Weight, approx.	300 g
last modified:	09.10.2015