



SIMATIC DP, ELECTRONIC MODULE F. ET 200S, 1 SSI 25BIT/1MHZ 15MM WIDE MODULE FOR CONN. OF ABSOLUTE ENCODERS WITH SSI INTERFACE SYNCHRONOUS SERIAL INTERFACE WITH DI AND COMPAR. VALUE WITH CLOCK CYCLIC SYNCHRON. APP

Supply voltage

Load voltage L+

• Rated value (DC)	24 V
• permissible range, lower limit (DC)	20.4 V
• permissible range, upper limit (DC)	28.8 V
• Reverse polarity protection	Yes

Input current

from load voltage L+ (without load), max.	40 mA
from backplane bus 3.3 V DC, max.	10 mA

Encoder supply

24 V encoder supply

• 24 V	Yes
• Short-circuit protection	Yes
• Output current, max.	500 mA

Absolute encoder (SSI) encoder supply

• Absolute encoder (SSI)	Yes
• Type of output voltage	L+ (-0.8 V)
• short-circuit protection	Yes

• Output current, max.	500 mA
Power loss	
Power loss, typ.	1 W
Hardware configuration	
Module exchange	
• Module exchange during operation of the IM-DP	Yes
• Module exchange under process voltage	Yes
Digital inputs	
Number of digital inputs	1
Input voltage	
• for signal "0"	-30 to +5V
• for signal "1"	+11 to +30V
Input current	
• for signal "0", max. (permissible quiescent current)	2 mA
• for signal "1", typ.	9 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— at "0" to "1", max.	300 µs
— at "1" to "0", max.	300 µs
Cable length	
• shielded, max.	50 m
Encoder	
Number of connectable encoders, max.	1
Connectable encoders	
• Absolute encoder (SSI)	Yes
• 2-wire sensor	Yes; Type 2
Encoder signals, absolute encoder (SSI)	
• Input signal	to RS-422
• Telegram length, parameterizable	13, 14, 16, 21, 24 & 25 bit
• Binary code	Yes
• Gray code	Yes
• Cable length, shielded, max.	320 m; At 125 kHz
• Monoflop time	16/32/48/64 µs
Interrupts/diagnostics/status information	
Diagnostics indication LED	
• Group error SF (red)	Yes
• Status indicator digital input (green)	Yes
• Status indicator backward counting (green)	Yes

- Status indicator forward counting (green)

Yes

Potential separation

Potential separation digital inputs

- Potential separation digital inputs

No; same potential with L+ and SSI

Potential separation counter

- between the channels and backplane bus
- Between the channels and load voltage L+

Yes

No

Dimensions

Width

15 mm

Height

81 mm

Depth

52 mm

Weights

Weight, approx.

40 g

last modified:

09/15/2017 