

Motor Starter Protectors/Circuit Breakers




SIRIUS 3RV2 Motor Starter Protectors/Circuit Breakers up to 40 A

Accessories

Mounting accessories

Selection and ordering data

Accessories

Version	For motor starter protectors/circuit breakers	DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*	PG
Size							
Covers							
 3RV2908-0P	Scale covers Sealable, for covering the set current scale	3RV20, 3RV21, 3RV24: S00, S0	▶ 3RV2908-0P		100	10 units	41E
 3RV2928-4AA00	Covers for devices with ring terminal lug connection (ensure finger-safety) • Main current level • For transverse auxiliary switches	3RV20: S00, S0	B B	Ring terminal lug connections  3RV2928-4AA00 3RV2908-4AA10	1 1	1 unit 1 unit	41E 41E
 3RV2908-4AA10							
Fixing accessories							
 3RV2928-0B	Push-in lugs For screwing the motor starter protector/ circuit breaker onto mounting plates For each motor starter protector/circuit breaker, two units are required.	S00, S0	A	3RV2928-0B	100	10 units	41E
Tools for opening spring-type terminals							
 3RA2908-1A	Screwdrivers For all SIRIUS devices with spring-type terminals Length approx. 200 mm, 3.0 mm x 0.5 mm, titanium gray/black, partially insulated	S00, S0	A	Spring-type terminals  3RA2908-1A	1	1 unit	41B
Terminal blocks and phase barriers for "Self-Protected Combination Motor Controllers (Type E)" according to UL 508							
 3RV2928-1H	Note: UL 508 demands 1-inch clearance and 2-inch creepage distance at line side for "Combination Motor Controller Type E". The following terminal blocks or phase barriers must be used in 3RV20 motor starter protectors. The terminal block or phase barriers cannot be used in combination with the 3RV19.5 three-phase busbars. For construction with three-phase busbars see "Busbar Accessories" page 7/29 onwards .						
 3RV2928-1K	Terminal blocks type E For extended clearance and creepage distances (1 and 2 inch)	S00, S0	▶	3RV2928-1H	1	1 unit	41E
	Phase barriers For extended clearance and creepage distances (1 and 2 inch)	S00, S0	▶	3RV2928-1K	1	1 unit	41E