

Terminal cover for busbar connections or on box terminal Size S6
from 3RT1, 3RB2, 3RW407, 3RW4



Product brand name	SIRIUS
Product designation	Covers for cable lug and busbar connections/length 100 mm
Design of the product	For complying with the voltage clearances and as touch protection (2 units required per contactor), suitable for S6 and S12 as well as mounted box terminals/can be used for 3UF71.3-1BA00-0, 3RW442. or 3RW443.

Certificates/approvals

General Product Approval	Functional Safety/Safety of Machinery	Declaration of Conformity	Marine / Shipping
--------------------------	---------------------------------------	---------------------------	-------------------



[Type Examination Certificate](#)



Marine / Shipping	other
-------------------	-------



[Confirmation](#)

other	Railway
-------	---------

[Miscellaneous](#)

[Vibration and Shock](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT1956-4EA1>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT1956-4EA1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT1956-4EA1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)


http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT1956-4EA1&lang=en

Characteristic: Tripping characteristics, I²t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RT1956-4EA1/char>

Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RT1956-4EA1&objecttype=14&gridview=view1>



last modified:

01/20/2019