



Figure similar

MLFB-Ordering data

6SL3225-0BE27-5AA1

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data	General tech. specifications																																												
Input <table> <tr> <td>Number of phases</td><td>3 AC</td></tr> <tr> <td>Line voltage</td><td>380 ... 480 V ± 10 %</td></tr> <tr> <td>Line frequency</td><td>47 ... 63 Hz</td></tr> <tr> <td>Rated current (LO)</td><td>25.00 A</td></tr> <tr> <td>Rated current (HO)</td><td>19.00 A</td></tr> </table>	Number of phases	3 AC	Line voltage	380 ... 480 V ± 10 %	Line frequency	47 ... 63 Hz	Rated current (LO)	25.00 A	Rated current (HO)	19.00 A	<table> <tr> <td>Power factor λ</td><td>0.90</td></tr> <tr> <td>Offset factor $\cos \varphi$</td><td>0.95</td></tr> <tr> <td>Efficiency η</td><td>0.95</td></tr> <tr> <td>Sound pressure level (1m)</td><td>60 dB</td></tr> <tr> <td>Power loss</td><td>0.28 kW</td></tr> <tr> <td>Filter class (integrated)</td><td>Class A</td></tr> </table>	Power factor λ	0.90	Offset factor $\cos \varphi$	0.95	Efficiency η	0.95	Sound pressure level (1m)	60 dB	Power loss	0.28 kW	Filter class (integrated)	Class A																						
Number of phases	3 AC																																												
Line voltage	380 ... 480 V ± 10 %																																												
Line frequency	47 ... 63 Hz																																												
Rated current (LO)	25.00 A																																												
Rated current (HO)	19.00 A																																												
Power factor λ	0.90																																												
Offset factor $\cos \varphi$	0.95																																												
Efficiency η	0.95																																												
Sound pressure level (1m)	60 dB																																												
Power loss	0.28 kW																																												
Filter class (integrated)	Class A																																												
Output <table> <tr> <td>Number of phases</td><td>3 AC</td></tr> <tr> <td>Rated voltage</td><td>400 V</td></tr> <tr> <td>Rated current (LO)</td><td>25.00 A</td></tr> <tr> <td>Rated current (HO)</td><td>19.00 A</td></tr> <tr> <td>Max. output current</td><td>38.00 A</td></tr> <tr> <td>Rated power IEC 400V (LO)</td><td>11.00 kW</td></tr> <tr> <td>Rated power NEC 480V (LO)</td><td>15.00 hp</td></tr> <tr> <td>Rated power IEC 400V (HO)</td><td>7.50 kW</td></tr> <tr> <td>Rated power NEC 480V (HO)</td><td>10.00 hp</td></tr> <tr> <td>Pulse frequency</td><td>4 kHz</td></tr> <tr> <td>Output frequency for vector control</td><td>0 ... 200 Hz</td></tr> <tr> <td>Output frequency for V/f control</td><td>0 ... 550 Hz</td></tr> </table>	Number of phases	3 AC	Rated voltage	400 V	Rated current (LO)	25.00 A	Rated current (HO)	19.00 A	Max. output current	38.00 A	Rated power IEC 400V (LO)	11.00 kW	Rated power NEC 480V (LO)	15.00 hp	Rated power IEC 400V (HO)	7.50 kW	Rated power NEC 480V (HO)	10.00 hp	Pulse frequency	4 kHz	Output frequency for vector control	0 ... 200 Hz	Output frequency for V/f control	0 ... 550 Hz	Ambient conditions <table> <tr> <td>Cooling</td><td>Internal air cooling</td></tr> <tr> <td>Cooling air requirement</td><td>0.038 m³/s (1.342 ft³/s)</td></tr> <tr> <td>Installation altitude</td><td>1000 m (3280.84 ft)</td></tr> <tr> <td>Ambient temperature</td><td></td></tr> <tr> <td>Operation LO</td><td>0 ... 40 °C (32 ... 104 °F)</td></tr> <tr> <td>Operation HO</td><td>0 ... 50 °C (32 ... 122 °F)</td></tr> <tr> <td>Transport</td><td>-25 ... 55 °C (-13 ... 131 °F)</td></tr> <tr> <td>Storage</td><td>-25 ... 55 °C (-13 ... 131 °F)</td></tr> <tr> <td>Relative humidity</td><td></td></tr> <tr> <td>Max. operation</td><td>95 % RH, condensation not permitted</td></tr> </table>	Cooling	Internal air cooling	Cooling air requirement	0.038 m ³ /s (1.342 ft ³ /s)	Installation altitude	1000 m (3280.84 ft)	Ambient temperature		Operation LO	0 ... 40 °C (32 ... 104 °F)	Operation HO	0 ... 50 °C (32 ... 122 °F)	Transport	-25 ... 55 °C (-13 ... 131 °F)	Storage	-25 ... 55 °C (-13 ... 131 °F)	Relative humidity		Max. operation	95 % RH, condensation not permitted
Number of phases	3 AC																																												
Rated voltage	400 V																																												
Rated current (LO)	25.00 A																																												
Rated current (HO)	19.00 A																																												
Max. output current	38.00 A																																												
Rated power IEC 400V (LO)	11.00 kW																																												
Rated power NEC 480V (LO)	15.00 hp																																												
Rated power IEC 400V (HO)	7.50 kW																																												
Rated power NEC 480V (HO)	10.00 hp																																												
Pulse frequency	4 kHz																																												
Output frequency for vector control	0 ... 200 Hz																																												
Output frequency for V/f control	0 ... 550 Hz																																												
Cooling	Internal air cooling																																												
Cooling air requirement	0.038 m ³ /s (1.342 ft ³ /s)																																												
Installation altitude	1000 m (3280.84 ft)																																												
Ambient temperature																																													
Operation LO	0 ... 40 °C (32 ... 104 °F)																																												
Operation HO	0 ... 50 °C (32 ... 122 °F)																																												
Transport	-25 ... 55 °C (-13 ... 131 °F)																																												
Storage	-25 ... 55 °C (-13 ... 131 °F)																																												
Relative humidity																																													
Max. operation	95 % RH, condensation not permitted																																												

Overload capability

Low Overload (LO)

1.1 x rated output current (i.e. 110 % overload) for 57 s with a cycle time of 300 s 1.5 x rated output current (i.e. 150 % overload) for 3 s with a cycle time of 300 s

High Overload (HO)

1.5 x output current rating (i.e., 150 % overload) for 57 s with a cycle time of 300 s 2 x output current rating (i.e., 200 % overload) for 3 s with a cycle time of 300 s

SIEMENS

Data sheet for SINAMICS Power Module PM250

MLFB-Ordering data

6SL3225-0BE27-5AA1




Figure similar

Mechanical data		Connections	
Degree of protection		Line side	
IP20 / UL open type			
Size		Version	
FSC		screw-type terminal	
Net weight		Conductor cross-section	
7.50 kg (16.53 lb)		2.50 ... 10.00 mm² (AWG 14 ... AWG 8)	
Width		Motor end	
189 mm (7.44 in)			
Height		Version	
334 mm (13.15 in)		Screw-type terminals	
Depth		Conductor cross-section	
185 mm (7.28 in)		2.50 ... 10.00 mm² (AWG 14 ... AWG 8)	

Converter losses to EN 50598-2*

Efficiency class	IE2
Comparison with the reference converter (90% / 100%)	-48.07 %



The percentage values show the losses in relation to the rated apparent power of the converter.

The diagram shows the losses for the points (as per standard EN 50598) of the relative torque generating current (I) over the relative motor stator frequency(f). The values are valid for the basic version of the converter without options/components.

*converted values

Max. motor cable length

Shielded	25 m (82.02 ft)
Unshielded	100 m (328.08 ft)

Standards

Compliance with standards	UL, cUL, CE, C-Tick (RCM)
---------------------------	---------------------------

CE marking	Low-voltage directive 2006/95/EC
------------	----------------------------------