

MLFB-Ordering data

6SL3210-1PE26-0UL0



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data		General tech. specifications	
Input		Power factor λ	0.95
Number of phases	3 AC	Offset factor $\cos \phi$	0.99
Line voltage	380 ... 480 V ± 10 %	Efficiency η	0.98
Line frequency	47 ... 63 Hz	Sound pressure level (1m)	72 dB
Rated current (LO)	57.00 A	Power loss	0.77 kW
Rated current (HO)	47.00 A	Ambient conditions	
Output		Cooling	Internal air cooling
Number of phases	3 AC	Cooling air requirement	0.055 m ³ /s
Rated voltage	400 V	Installation altitude	1000 m
Rated power (LO)	30.00 kW / 40.00 hp	Ambient temperature	
Rated power (HO)	22.00 kW / 30.00 hp	Operation LO	-20 ... 40 °C (-4 ... 104 °F)
Rated current (LO)	60.00 A	Operation HO	-20 ... 50 °C (-4 ... 122 °F)
Rated current (HO)	45.00 A	Transport	-40 ... 70 °C (-40 ... 158 °F)
Max. output current	90.00 A	Storage	-40 ... 70 °C (-40 ... 158 °F)
Pulse frequency	4 kHz	Relative humidity	
Output frequency for vector control	0 ... 200 Hz	Max. operation	95 % RH, condensation not permitted
Output frequency for V/f control	0 ... 550 Hz		

Overload capability

Low Overload (LO)

1.1 x rated output current (i.e. 110 % overload) for 57 s with a cycle time of 300 s 1.5 x rated output current (i.e. 150 % overload) for 3 s with a cycle time of 300 s

High Overload (HO)

1.5 x output current rating (i.e., 150 % overload) for 57 s with a cycle time of 300 s 2 x output current rating (i.e., 200 % overload) for 3 s with a cycle time of 300 s

SIEMENS

Data sheet for SINAMICS Power Module PM240-2



MLFB-Ordering data

6SL3210-1PE26-0UL0

Mechanical data		Connections	
Degree of protection	IP20	Line side	
Size	FSD	Version	screw-type terminal
Net weight	17.00 kg	Conductor cross-section	10.00 ... 35.00 mm²
Width	200.0 mm	Motor end	
Height	472.0 mm	Version	Screw-type terminals
Depth	237.0 mm	Conductor cross-section	10.00 ... 35.00 mm²
Converter losses to EN 50598-2*		DC link (for braking resistor)	
Efficiency class	IE2	Version	Screw-type terminals
Comparison with the reference converter (90% / 100%)	-58.52 %	Conductor cross-section	2.50 ... 16.00 mm²
		PE connection	Screw-type terminals
		Max. motor cable length	
		Shielded	200 m
		Unshielded	300 m
Standards			
Compliance with standards		UL, cUL, CE, C-Tick (RCM), SEMI F47	
CE marking		Low-voltage directive 2006/95/EC	

The percentage values show the losses in relation to the rated apparent power of the converter.

The diagram shows the losses for the points (as per standard EN 50598) of the relative torque generating current (I) over the relative motor stator frequency(f). The values are valid for the basic version of the converter without options/components.

*converted values