

I/O systems

SIMATIC ET 200 systems without control cabinet

SIMATIC ET 200eco PN

Overview



- Compact block I/O for processing digital, analog and IO-Link signals for connecting to the PROFINET bus system
- Cabinet-free design in IP65/66/67 degree of protection with M12 connections
- Extremely rugged and resistant metal enclosure and casting
- Compact module in two types of enclosures:
 - 30 mm x 200 mm x 37 mm (W x H x D, long and narrow enclosure), with 4 x M12 for digital signals
 - 60 mm x 175 mm x 37 mm (W x H x D, short and wide enclosure), with 8 x M12 for digital signals and IO-Link
 - 60 mm x 175 mm x 37 mm (W x H x D, short and wide enclosure) with 4 x M12 or 8 x M12 for analog signals
- PROFINET connection: 2 x M12 and automatic PROFINET address assignment
- Data transmission rate 100 Mbps
- LLDP proximity detection without PG and fast startup (boot up within approx. 0.5 seconds)
- Supply and load voltage connection: 2 x M12
- Module variance:
 - 8 DI
 - 16 DI
 - 8 DO (2 A)
 - 8 DO (1.3 A)
 - 8 DO (0.5 A)
 - 16 DO (1.3 A)
 - 8 DI/DO (1.3 A)
 - 8 AI (U, I, TC, RTD)
 - 8 AI (TC, RTD)
 - 4 AO (U, I)
 - 4 IO-Link
 - 4 IO-Link + 8 DI + 4 DO (1.3 A)
- Channel-specific diagnostics
- Ambient temperature range -40 °C to 60 °C

Technical specifications

Article number	6ES7141-6BF00-0AB0	6ES7141-6BG00-0AB0	6ES7141-6BH00-0AB0
	ET 200ECO PN, 8DI, DC24V, 4XM12	ET 200ECO PN, 8DI, DC24V, 8XM12	ET 200ECO PN, 16DI, DC24V, 8XM12
General information			
Vendor identification (VendorID)	002AH	002AH	002AH
Device identifier (DeviceID)	0306H	0306H	0306H
Supply voltage			
Rated value (DC)	24 V	24 V	24 V
Reverse polarity protection	Yes	Yes	Yes
Input current			
Current consumption, typ.	100 mA	100 mA	100 mA
Encoder supply			
Number of outputs	4	8	8
Short-circuit protection	Yes; Electronic	Yes; Electronic	Yes; Electronic
Output current			
• Rated value	100 mA; per output	100 mA; per output	100 mA; per output
Power loss			
Power loss, typ.	5.5 W	4.5 W	6.5 W
Digital inputs			
Number of digital inputs	8	8	16
• in groups of	2	1	2
Input characteristic curve in accordance with IEC 61131, type 3	Yes	Yes	Yes
Number of simultaneously controllable inputs			
all mounting positions			
- up to 60 °C, max.	8	8	16

Technical specifications (continued)

Article number	6ES7141-6BF00-0AB0 ET 200ECO PN, 8DI, DC24V, 4XM12	6ES7141-6BG00-0AB0 ET 200ECO PN, 8DI, DC24V, 8XM12	6ES7141-6BH00-0AB0 ET 200ECO PN, 16DI, DC24V, 8XM12
Input voltage			
• Type of input voltage	DC	DC	DC
• Rated value (DC)	24 V	24 V	24 V
• for signal "0"	-3 to +5V	-3 to +5V	-3 to +5V
• for signal "1"	+11 to +30V	+11 to +30V	+11 to +30V
Input current			
• for signal "1", typ.	7 mA	7 mA	7 mA
Input delay (for rated value of input voltage) for standard inputs			
- at "0" to "1", max.	typically 3 ms	typically 3 ms	typically 3 ms
- at "1" to "0", max.	typically 3 ms	typically 3 ms	typically 3 ms
Cable length			
• unshielded, max.	30 m	30 m	30 m
Encoder			
Connectable encoders			
• 2-wire sensor	Yes	Yes	Yes
- permissible quiescent current (2-wire sensor), max.	1.5 mA	1.5 mA	1.5 mA
Interfaces			
Transmission procedure	100BASE-TX	100BASE-TX	100BASE-TX
Number of PROFINET interfaces	1	1	1
PROFINET IO			
• Autocrossing	Yes	Yes	Yes
• automatic detection of transmission rate	Yes	Yes	Yes
• Transmission rate, max.	100 Mbit/s	100 Mbit/s	100 Mbit/s
• integrated switch	Yes	Yes	Yes
PROFINET IO Device			
- IRT with the option "high flexibility"	Yes	Yes	Yes
- Prioritized startup	Yes	Yes	Yes
Protocols			
Supports protocol for PROFINET IO	Yes	Yes	Yes
PROFINET CBA	No	No	No
PROFIsafe	No	No	No
Protocols (Ethernet)			
• TCP/IP	No	No	No
• SNMP	Yes	Yes	Yes
• DCP	Yes	Yes	Yes
• LLDP	Yes	Yes	Yes
• ping	Yes	Yes	Yes
• ARP	Yes	Yes	Yes
Interrupts/diagnostics/ status information			
Status indicator	Yes; Green LED	Yes; Green LED	Yes; Green LED
Diagnostic functions	Yes	Yes	Yes
Alarms			
• Diagnostic alarm	Yes	Yes	Yes
Diagnostic messages			
• Diagnostic information readable	Yes	Yes	Yes
• Monitoring the supply voltage	Yes; Green "ON" LED	Yes; Green "ON" LED	Yes; Green "ON" LED
• Wire-break in signal transmitter cable	Yes	Yes	Yes
• Short-circuit encoder supply	Yes; Per channel group	Yes; Per channel group	Yes; Per channel group
• Group error	Yes; Red/yellow "SF/MT" LED	Yes; Red/yellow "SF/MT" LED	Yes; Red/yellow "SF/MT" LED

I/O systems

SIMATIC ET 200 systems without control cabinet

SIMATIC ET 200eco PN

Technical specifications (continued)

Article number	6ES7141-6BF00-0AB0 ET 200ECO PN, 8DI, DC24V, 4XM12	6ES7141-6BG00-0AB0 ET 200ECO PN, 8DI, DC24V, 8XM12	6ES7141-6BH00-0AB0 ET 200ECO PN, 16DI, DC24V, 8XM12
Potential separation			
between the load voltages	Yes	Yes	Yes
between load voltage and all other switching components	No	No	No
between Ethernet and electronics	Yes	Yes	Yes
Potential separation digital inputs			
• between the channels	No	No	No
Isolation			
tested with			
• 24 V DC circuits	707 V DC (type test)	707 V DC (type test)	707 V DC (type test)
• Interface	1 500 V; According to IEEE 802.3	1 500 V; According to IEEE 802.3	1 500 V; According to IEEE 802.3
Degree and class of protection			
IP degree of protection	IP65/67	IP67	IP67
Connection method			
Design of electrical connection	4/5-pin M12 circular connectors	4/5-pin M12 circular connectors	4/5-pin M12 circular connectors
Dimensions			
Width	30 mm	60 mm	60 mm
Height	200 mm	175 mm	175 mm
Depth	49 mm	49 mm	49 mm
Weights			
Weight (without packaging)	550 g	910 g	910 g

Article number	6ES7142-6BF50-0AB0 ET 200ECO PN, 8DO, DC24V/0.5A, 4XM12	6ES7142-6BF00-0AB0 ET 200ECO PN, 8DO, DC24V/1.3A, 4XM12	6ES7142-6BG00-0AB0 ET 200ECO PN, 8DO, DC24V/1.3A, 8XM12	6ES7142-6BR00-0AB0 ET 200ECO PN, 8 DO, DC24V/2A, 8XM12	6ES7142-6BH00-0AB0 ET 200ECO PN, 16DO, DC24V/1.3A, 8XM12
General information					
Vendor identification (VendorID)	002AH	002AH	002AH	002AH	002AH
Device identifier (DeviceID)	0306H	0306H	0306H	0306H	0306H
Supply voltage					
Rated value (DC)	24 V	24 V	24 V	24 V	24 V
Reverse polarity protection	Yes	Yes	Yes	Yes	Yes
Load voltage 2L+					
• Rated value (DC)	24 V	24 V	24 V	24 V	24 V
• Reverse polarity protection	Yes	Yes	Yes	Yes	Yes
Input current					
Current consumption, typ.	100 mA	100 mA	100 mA	100 mA	100 mA
from supply voltage 1L+, max.	4 A	4 A	4 A	4 A	4 A
from load voltage 2L+, max.	4 A	4 A	4 A	4 A	4 A
Power loss					
Power loss, typ.	3 W	5.5 W	5.5 W	5 W	5.5 W
Digital outputs					
Number of digital outputs	8	8	8	8	16
• in groups of	8	4	4	4	8
Short-circuit protection	Yes	Yes	Yes	Yes	Yes
• Response threshold, typ.	0.7 A	1.8 A	1.8 A	2.8 A	1.8 A
Limitation of inductive shutdown voltage to	Typ. (L1+, L2+) -47 V	Typ. (L1+, L2+) -47 V	Typ. (L1+, L2+) -47 V	Typ. (L1+, L2+) -47 V	Typ. (L1+, L2+) -47 V
Controlling a digital input	Yes	Yes	Yes	Yes	Yes
Switching capacity of the outputs					
• on lamp load, max.	5 W	5 W	5 W	10 W	5 W
Output current					
• for signal "1" rated value	0.5 A	1.3 A; Maximum	1.3 A; Maximum	2 A	1.3 A; Maximum
• for signal "0" residual current, max.	1.5 mA	1.5 mA	1.5 mA	1.5 mA	1.5 mA