

SIMATIC DP, INTERFACE MODULE IM151-3 PN FO FOR ET 200S
2 PROFINET FO INTERFACES INTEGRATED 2-PORT SWITCH
MAX. OF 63 PERIPHERAL MODULES USABLE FOR PROFISAFE
MODULES MAX. 2M STATION WIDTH INCL. TERMINATING
MODULE



Figure similar

Configuration control	
via dataset	Yes
Supply voltage	
Mains buffering	
• Mains/voltage failure stored energy time	20 ms
Input current	
from supply voltage 1L+, max.	200 mA
Power loss	
Power loss, typ.	5 W
Address area	
Addressing volume	
• Inputs	256 byte
• Outputs	256 byte
Interfaces	
Number of PROFINET interfaces	1

Interface physics, FOC	Yes
PROFINET IO	
• Autocrossing	Yes
• automatic detection of transmission rate	Yes
• Transmission rate, max.	100 Mbit/s
• RJ 45	Yes
Protocols	
Supports protocol for PROFINET IO	Yes
MRP	Yes
Protocols (Ethernet)	
• SNMP	Yes
• LLDP	Yes
• ping	Yes
• ARP	Yes
PROFINET IO Device	
Services	
— Isochronous mode	No
— IRT	Yes
— PROFINET energy	Yes
— Prioritized startup	Yes
— Shared device	Yes
— Number of IO Controllers with shared device, max.	2
Interrupts/diagnostics/status information	
Alarms	Yes
Diagnostic functions	Yes
Diagnostics indication LED	
• Bus fault BF (red)	Yes
• Group error SF (red)	Yes
• Monitoring 24 V voltage supply ON (green)	Yes
• Connection to network LINK (green)	Yes
Potential separation	
between Ethernet and electronics	Yes
Permissible potential difference	
between different circuits	75 V DC/60 V AC
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes
Ambient conditions	
Ambient temperature during operation	

- min.
- max.

0 °C
60 °C

Dimensions

Width	60 mm
Height	119.5 mm
Depth	75 mm; with mounting rail

Weights

Weight, approx.	150 g
-----------------	-------

last modified: 11/28/2017